



ABOX

Assortments heat shrink tubing

Features:

- Crosslinked Polyolefin • Shrink ratio: 2:1 • Flame retardant
- General purpose • High flexibility

Application:

- Operating temperature: -55 °C to +125 °C • Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C • Longitudinal change: 0 ± 10% max.

For electronic, automotive and consumer goods.

Flexible, flame retardant, low shrinking temperature.

Free from harmful substances such as PBB's, PBBO's, PBBE's.

ABOX 1: 127 pcs ACS-55 heat shrink tubing (mixed colors)

Type / Size	Length in mm	Quantity
ACS-55 1,6/0,8	35,0	30
ACS-55 2,4/1,2	35,0	25
ACS-55 3,2/1,6	35,0	20
ACS-55 4,8/2,4	35,0	20
ACS-55 6,4/3,2	70,0	16
ACS-55 9,5/4,8	70,0	8
ACS-55 12,7/6,4	80,0	8



ABOX 2: 127 pcs ACS-55 heat shrink tubing (black)

Type / Size	Length in mm	Quantity
ACS-55 1,6/0,8	35,0	30
ACS-55 2,4/1,2	35,0	25
ACS-55 3,2/1,6	35,0	20
ACS-55 4,8/2,4	35,0	20
ACS-55 6,4/3,2	70,0	16
ACS-55 9,5/4,8	70,0	8
ACS-55 12,7/6,4	80,0	8



ABOX 3: 465 pcs ACS-55 heat shrink tubing (black)

Type / Size	Length in mm	Quantity
ACS-55 2,4/1,2	35,0	120
ACS-55 3,2/1,6	35,0	100
ACS-55 4,8/2,4	35,0	80
ACS-55 6,4/3,2	35,0	60
ACS-55 9,5/4,8	70,0	65
ACS-55 12,7/6,4	70,0	15
ACS-55 16,0/8,0	100,0	15
ACS-55 19,0/9,5	70,0	5
ACS-55 25,4/12,7	70,0	5



We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.