



## AMB-DW

Dual-wall heat shrink tubing, flexible, flame retardant, 3:1, adhesive lined

### Features:

- Crosslinked co-extruded adhesive lined Polyolefin • Shrink ratio: 3:1
- Flame retardant • Excellent sealing and insulation properties • UV resistant

### Approvals:

- UL224 125 °C VW-1 600 V file E204071 • Meets: RoHS
- Meets: SAE-AMS-DTL-23053/4

### Application:

- Operating temperature: -55 °C to +125 °C • Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +110 °C • Longitudinal change: 0 ± 10% max.

### Order information:

Color: black



Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Box / Meter
AMB-DW 3:1 3,0/1,0	3,0	1,0	1,00	5,0
AMB-DW 3:1 4,8/1,5	4,8	1,5	1,00	5,0
AMB-DW 3:1 6,0/2,0	6,0	2,0	1,00	3,5
AMB-DW 3:1 9,0/3,0	9,0	3,0	1,40	3,0
AMB-DW 3:1 12,0/4,0	12,0	4,0	1,60	2,5
AMB-DW 3:1 19,0/6,0	19,0	6,0	2,15	2,0
AMB-DW 3:1 24,0/8,0	24,0	8,0	2,40	1,5

*We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.*