



CABLE TIES RELEASE - PUSH MOUNT

ATIE OPEN

RELEASE

Material : Polyamide 6.6
 Color : Transparent / black (UV resistant)
 : Other colors available on request
 Temperature range : -40 °C up to +85 °C
 Flammability : UL 94 V2
 Certification : UL, Lloyd's



Width up to and including 4,8 mm




Width 7,6 mm



Typenr.	Length (mm)	Width (mm)	Max. bundle diameter (mm)	Tensile strength (kg)	Packing (pcs)
RELEASE 140x3,6mm	140	3,6	33	18,2	100
RELEASE 200x4,8mm	200	4,8	50	22,2	100
RELEASE 300x4,8mm	300	4,8	86	22,2	100
RELEASE 370x4,8mm	370	4,8	102	22,2	100
RELEASE 120x7,6mm	120	7,6	30	22,2	100
RELEASE 150x7,6mm	150	7,6	35	22,2	100
RELEASE 200x7,6mm	200	7,6	50	22,2	100
RELEASE 250x7,6mm	250	7,6	66	22,2	100
RELEASE 300x7,6mm	300	7,6	80	22,2	100
RELEASE 370x7,6mm	370	7,6	102	22,2	100

PUSH MOUNT

Material : Polyamide 6.6
 Color : Transparent / black (UV resistant)
 : Other colors available on request
 Temperature range : -40 °C up to +85 °C
 Flammability : UL 94 V2
 Certification : UL, Lloyd's



Typenr.	Length (mm)	Width (mm)	Max. bundle diameter (mm)	Tensile strength (kg)	Pack- ing (pcs)	Hole diameter (mm)	Panel thickness (mm)	Type
PUSH MOUNT 110x2,5mm	110	2,5	22	8,1	100	Ø 4,8	~ 2,4	1
PUSH MOUNT 130x3,2mm	130	3,2	28	13,6	100	Ø 4,0	~ 2,0	1
PUSH MOUNT 130x4,8mm	130	4,8	25	22,2	100	Ø 6,4	~ 3,2	1
PUSH MOUNT 170x4,8mm	170	4,8	38	22,2	100	Ø 6,4	~ 3,2	1
PUSH MOUNT 190x4,8mm	190	4,8	45	22,2	100	Ø 6,4	~ 3,2	1
PUSH MOUNT 150x3,6mm	150	3,6	32	13,6	100	Ø 5,2	~ 2,8	2
PUSH MOUNT 200x4,8mm	200	4,8	46	22,2	100	Ø 6,3	~ 3,6	2

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.