

## POLYAMIDE 6.6 CABLE TIES NATURAL - EUROSLOT PACKAGING

Ty-Rap® high performance cable ties

### Characteristics:

- Standard version (Polyamide 6.6), to cover most indoor applications
- Packaging in small polythene bags with Euroslot, ideal for display and point-of-sales promotion (rack)
- Several lengths and 5 typical widths with a tensile strength up to 540N, to cover the most demanding applications
- Very convenient for small series production: 100 pieces (for cable ties from 2.3 mm to 4.8 mm width) or 50 pieces (for cable ties 6.9 mm width and above)



### Technical information:

Material - Moulding	: Polyamide 6.6
Material - Locking barb	: 316 grade stainless steel
Temperature range	: -60 °C up to +85 °C
Min. installation temp.	: -20 °C
Colour	: Natural
Flammability rating	: UL 94 V-2
Other properties	: Halogen free, silicone free



Product Ref.	MIL Spec.	Length L [mm]	Width W [mm]	Thickness [mm]	Bundle ø from ... to [mm]	Min. tensile strength [N]	Quantity [pieces]
TY523MR	MS-3367-4	92	2.3	1.0	1.5 - 22	80	100
TY5232MR	–	203	2.3	1.0	1.5 - 51	80	100
TY5234M	–	356	2.3	1.0	1.5 - 102	80	100
TY524MR	MS-3367-5	140	3.6	1.1	2 - 35	178	100
TY5242MR	–	208	3.6	1.1	2 - 51	180	100
TY526MR	–	284	3.6	1.1	2 - 76	130	100
TY5244MR	–	368	3.6	1.1	2 - 102	134	100
TY525MR	MS-3367-1	186	4.8	1.1	3 - 48	222	100
TY5253MR	MS-3367-7	290	4.8	1.3	3 - 78	222	100
TY528MR	MS-3367-2	361	4.8	1.3	3 - 102	222	100
TY5271MR	–	150	7.0	1.6	6 - 31	540	50
TY5272MR	–	223	6.9	1.6	6 - 51	534	50
TY527MR	MS-3367-3	340	7.0	1.6	6 - 102	540	50
TY5275M	–	457	7.0	1.6	6 - 127	540	50
TY5277M	–	617	7.0	1.6	6 - 177	540	50
TY529M	MS-3367-6	771	6.9	1.5	6 - 229	540	50

Product References TY5234M, TY5275M, TY5277M and TY529M have no Euroslot



\* Some approvals may not be applicable to all the Product References.

*We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.*