

## POLYAMIDE 6.6 CABLE TIES - WORKBENCH BOXES

Ty-Rap® high performance cable ties

### Characteristics:


- An attractive packaging option for high volume manual assembly: 1000 pieces in a workbench box - easy to reach, hence timesaving
- This user-friendly packaging allows fast working without problems or losses

### Technical information:

Material - Moulding	: Polyamide 6.6
Material - Locking barb	: 316 grade stainless steel
Temperature range	: -60 °C up to +85 °C (natural) : -60 °C up to +105 °C (black)
Min. installation temp.	: -20 °C (natural) : -30 °C (black)
Colour	: Natural or UV-resistant black
Flammability rating	: UL 94 V-2
Other properties	: Halogen free, silicone free, UV-resistant (black)



Product Ref.	MIL Spec.	Colour	Length L [mm]	Width W [mm]	Thickness [mm]	Bundle ø from ... to [mm]	Min. tensile strength [N]	Quantity [pieces]
TYB23M	MS-3367-4	natural	92	2.3	1.0	1.5 - 22	80	1000
TYB23MX	MS-3367-4	UV-resistant black	92	2.3	1.0	1.5 - 22	80	1000
TYB232M	-	natural	203	2.3	1.0	1.5 - 51	80	1000
TYB232MX	-	UV-resistant black	203	2.3	1.0	1.5 - 51	80	1000
TYB24M	MS-3367-5	natural	140	3.6	1.1	2 - 35	178	1000
TYB24MX	MS-3367-5	UV-resistant black	140	3.6	1.1	2 - 35	180	1000
TYB25M	MS-3367-1	natural	186	4.8	1.3	3 - 48	222	1000
TYB25MX	MS-3367-1	UV-resistant black	186	4.8	1.3	3 - 48	220	1000



\* Some approvals may not be applicable to all the Product References.

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.