

**TERMINALS**  
NON-INSULATED CORD END TERMINALS

MATERIAL: Copper alloy  
PLATING: Electro tin plated  
MIN. COATING THICKNESS 3 µm

• RoHS compliant

\* These items are also available in bags of 100 pcs



PRT NR.	WIRERANGE MM <sup>2</sup>	L	C	W	PACKED	UL
AH 0.14*	0.14	7	0.65	1.6	1000	
AH 0.25K*	0.25	5	0.75	1.7	1000	
AH 0.25*	0.25	7	0.75	1.7	1000	
AH 0.25L*	0.25	10	0.75	1.7	1000	
AH 0.34K*	0.34	5	0.85	1.8	1000	
AH 0.34*	0.34	7	0.85	1.8	1000	
AH 0.50KK*	0.5	6	1	2.1	1000	Y
AH 0.50K*	0.5	8	1	2.1	1000	Y
AH 0.50*	0.5	10	1	2.1	1000	Y
AH 0.75KK*	0.75	6	1.2	2.3	1000	Y
AH 0.75K*	0.75	8	1.2	2.3	1000	Y
AH 0.75*	0.75	10	1.2	2.3	1000	Y
AH 0.75HL*	0.75	12	1.2	2.3	1000	Y
AH 1.00KK*	1.0	6	1.4	2.5	1000	Y
AH 1.00K*	1.0	8	1.4	2.5	1000	Y
AH 1.00*	1.0	10	1.4	2.5	1000	Y
AH 1.00HL*	1.0	12	1.4	2.5	1000	Y
AH 1.50KK*	1.5	7	1.7	2.8	1000	Y
AH 1.50K*	1.5	8	1.7	2.8	1000	Y
AH 1.50*	1.5	10	1.7	2.8	1000	Y
AH 1.50HL*	1.5	12	1.7	2.8	1000	Y
AH 2.50KK*	2.5	7	2.2	3.4	1000	Y
AH 2.50K*	1.5	8	2.2	3.4	1000	Y
AH 2.50*	2.5	10	2.2	3.4	1000	Y
AH 2.50HL*	2.5	12	2.2	3.4	1000	Y
AH 2.50L*	2.5	18	2.2	3.4	1000	Y
AH 4.00K*	4.0	9	2.8	4	1000	Y
AH 4.00N*	4.0	10	2.8	4	1000	Y
AH 4.00*	4.0	12	2.8	4	1000	Y
AH 4.00HL*	4.0	15	2.8	4	1000	Y
AH 4.00L*	4.0	18	2.8	4	1000	Y

For other types, please see the following page

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.

PRT NR.	WIRERANGE MM <sup>2</sup>	L	C	W	PACKED	UL
AH 6.00K*	6.0	10	3.5	4.7	250	Y
AH 6.00HL*	6.0	12	3.5	4.7	250	Y
AH 6.00*	6.0	15	3.5	4.7	250	Y
AH 6.00L*	6.0	18	3.5	4.7	250	Y
AH 10.00K*	10.0	12	4.5	5.8	250	Y
AH 10.00*	10.0	15	4.5	5.8	250	Y
AH 10.00L*	10.0	18	4.5	5.8	250	Y
AH 16.00K*	16.0	12	5.8	7.5	250	Y
AH 16.00*	16.0	15	5.8	7.5	250	Y
AH 16.00HL*	16.0	18	5.8	7.5	250	Y
AH 16.00L*	16.0	25	5.8	7.5	250	Y
AH 25.00KK*	25.0	12	7.3	9.5	250	Y
AH 25.00K*	25.0	15	7.3	9.5	250	Y
AH 25.00*	25.0	18	7.3	9.5	250	Y
AH 25.00HL*	25.0	25	7.3	9.5	250	Y
AH 25.00L*	25.0	32	7.3	9.5	250	Y
AH 35.00K	35.0	12	8.3	11	100	Y
AH 35.00	35.0	18	8.3	11	100	Y
AH 35.00HL	35.0	20	8.3	11	100	Y
AH 35.00L	35.0	25	8.3	11	100	Y
AH 50.00K	50.0	18	10.3	13	100	Y
AH 50.00	50.0	22	10.3	13	100	Y
AH 50.00HL	50.0	25	10.3	13	100	Y
AH 50.00L	50.0	32	10.3	13	100	Y
AH 70.00HL	70.0	25	12.5	15	100	
AH 70.00L	70.0	32	12.5	15	100	
AH 95.00HL	95.0	25	14.5	17	50	
AH 95.00L	95.0	32	14.5	17	50	
AH 120.00HL	120.0	32	16.5	19	50	
AH 150.00HL	150.0	32	18.5	21	50	
AH 150.00L	150.0	38	18.5	21	50	

*We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.*