

CORRUGATED TUBING PA6

Material : Polyamide 6
 Protection rating : IP 68
 Flame class : UL 94 HB
 Temperature range : -40 °C up to +120 °C
 : short term +150 °C

On request also slotted and in Polypropylene available

Applications:

Machine and plant constructions, automotive, shipbuilding, automation, electrical installations.

Mechanical protection for cables and conductors, pressure and impact resistant, flexible, high tensile and compressive strength.



Typenr.	DN	Inside diameter (mm)	Outside diameter (mm)	Bending radius (mm)	Packing (mtr)
Corrugated tubing DN 7,5	7,5	6,9	9,9	13,0	50
Corrugated tubing DN 8,5	8,5	8,4	11,4	15,0	50
Corrugated tubing DN 10,0	10,0	9,9	13,0	20,0	50
Corrugated tubing DN 12,0	12,0	12,2	15,7	30,0	50
Corrugated tubing DN 13,0	13,0	12,7	15,8	35,0	50
Corrugated tubing DN 14,0	14,0	14,2	18,5	40,0	50
Corrugated tubing DN 17,0	17,0	16,6	21,2	45,0	50
Corrugated tubing DN 22,0	22,0	21,2	25,5	50,0	50
Corrugated tubing DN 23,0	23,0	23,2	28,3	55,0	50
Corrugated tubing DN 26,0	26,0	25,7	32,2	60,0	50
Corrugated tubing DN 29,0	29,0	29,0	34,5	65,0	25
Corrugated tubing DN 36,0	36,0	36,0	42,4	90,0	25
Corrugated tubing DN 50,0	50,0	48,1	53,8	100,0	25
Corrugated tubing DN 56,0	56,0	56,3	67,2	130,0	30
Corrugated tubing DN 65,0	65,0	62,7	73,5	145,0	10
Corrugated tubing DN 70,0	70,0	67,5	80,0	160,0	10
Corrugated tubing DN 95,0	95,0	91,5	106,0	210,0	10

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.