


TERMINALS**PVC insulated spade terminals**

Maximum electrical rating : 600 V max.
 Maximum temperature : 75 °C
 Insulation material : PVC
 Terminal material : Copper

Also available without sleeve and with "easy entry"

RoHS compliant



PRT NR.	WIRE RANGE (MM ²)	COLOR	D2	B	L	F	E	D	D1	PACKED
RBFV 1.25-B3A	0.5~1.5	red	3.2	5.7	21	6.5	10	4.3	1.7	10 x 100
RBFV 1.25-YS3A	0.5~1.5	red	3.7	6.4	21	6.5	10	4.3	1.7	10 x 100
RBFV 1.25-YS4A	0.5~1.5	red	4.3	6.4	21	6.5	10	4.3	1.7	10 x 100
RBFV 1.25-S4A	0.5~1.5	red	4.3	7.2	21	6.5	10	4.3	1.7	10 x 100
RBFV 1.25-5A	0.5~1.5	red	5.3	8.1	21	6.5	10	4.3	1.7	10 x 100
RBFV 1.25-6A	0.5~1.5	red	6.4	9.5	21	6.5	10	4.3	1.7	10 x 100
BVF 1.25-8A	0.5~1.5	red	8.4	12	27.2	11	10	4.1	1.7	10 x 100
RBFV 2-B3A	1.5~2.5	blue	3.2	5.7	21	6.5	10	4.8	2.3	10 x 100
RBFV 2-YS3A	1.5~2.5	blue	3.7	6	21	6.5	10	4.8	2.3	10 x 100
RBFV 2-S3A	1.5~2.5	blue	3.7	7.2	21	6.5	10	4.8	2.3	10 x 100
RBFV 2-YS4A	1.5~2.5	blue	4.3	6.4	21	6.5	10	4.8	2.3	10 x 100
RBFV 2-S4A	1.5~2.5	blue	4.3	7.2	21	6.5	10	4.8	2.3	10 x 100
RBFV 2-S4LA	1.5~2.5	blue	4.3	7.9	21	6.5	10	4.8	2.3	10 x 100
RBFV 2-5A	1.5~2.5	blue	5.3	7.9	21	6.5	10	4.8	2.3	10 x 100
RBFV 2-S5A	1.5~2.5	blue	5.3	9.3	21	6.5	10	4.8	2.3	10 x 100
RBFV 2-6A	1.5~2.5	blue	6.4	12	27.5	11	10	4.8	2.3	10 x 100
RBFV 5.5-3A	4~6	yellow	3.7	8.3	25.5	7	13	6.2	3.4	10 x 100
RBFV 5.5-S4A	4~6	yellow	4.3	8.3	25.5	7	13	6.2	3.4	10 x 100
RBFV 5.5-4LA	4~6	yellow	4.3	9	25.5	7	13	6.2	3.4	10 x 100
RBFV 5.5-5A	4~6	yellow	5.3	9	25.5	7	13	6.2	3.4	10 x 100
RBFV 5.5-6A	4~6	yellow	6.4	12	31.5	12	13	6.2	3.4	10 x 100
RBFV 5.5-8A	4~6	yellow	8.4	14	30.5	11.5	13	6.2	3.4	10 x 100

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.