

TERMINALS
PP INSULATED TWIN WIRE CORD END TERMINALS

MAX. OPERATING TEMP: 105 °C
MATERIAL: Copper alloy
PLATING: Electro tin plated
MIN. COATING THICKNESS: 3 µm
INSULATION: PP

• RoHS compliant

* These items are also available in bags of 100 pcs

** These items have no UL certification



PRT NR.	COLOR	WIRERANGE AWG	WIRERANGE MM ²	F	L	C	W	UL	PACKED
TAHV 0.25N*	violet	2 x 24	2 x 0.25	8	15	1.15	3.4		500
TAHB 0.25N*	blue	2 x 24	2 x 0.25	8	15	1.15	3.4		500
TAHT 0.34N*	turquoise	2 x 22	2 x 0.34	8	15	1.15	3.5		500
TAHW 0.50N*	white	2 x 20	2 x 0.5	8	15	1.4	4.7	Y	500
TAHO 0.50N*	orange	2 x 20	2 x 0.5	8	15	1.4	4.7	Y	500
TAHB 0.75N*	blue	2 x 18	2 x 0.75	8	15	1.7	5	Y	500
TAHW 0.75N*	white	2 x 18	2 x 0.75	8	15	1.7	5	Y	500
TAHGRS 0.75N*	gray	2 x 18	2 x 0.75	8	15	1.7	5	Y	500
TAHR 1.00N*	red	2 x 17	2 x 1.0	8	15	1.95	5.4	Y	500
TAHG 1.00N*	yellow	2 x 17	2 x 1.0	8	15	1.95	5.4	Y	500
TAHZ 1.50N*	black	2 x 15	2 x 1.5	8	16	2.2	6.6	Y	500
TAHR 1.50N*	red	2 x 15	2 x 1.5	8	16	2.2	6.6	Y	500
TAHGRS 2.50N*	gray	2 x 13	2 x 2.5	10	18.5	2.8	7.8	Y	250
TAHB 2.50N*	blue	2 x 13	2 x 2.5	10	18.5	2.8	7.8	Y	250
TAHO 4.00N	orange	2 x 11	2 x 4.0	12	23	3.7	8.8	Y	100
TAHGRS 4.00N	gray	2 x 11	2 x 4.0	12	23	3.7	8.8	Y	100
TAHGR 6.00N	green	2 x 9	2 x 6.0	14	26	4.8	10	Y	100
TAHZ 6.00N**	black	2 x 9	2 x 6.0	14	26	4.8	10	Y	100
TAHG 6.00N	yellow	2 x 9	2 x 6.0	14	26	4.8	10	Y	100
TAHBR 10.00N	brown	2 x 7	2 x 10.0	14	26	6.4	13	Y	100
TAHCR 10.00N	cream	2 x 7	2 x 10.0	14	26	6.4	13	Y	100
TAHR 10.00N	red	2 x 7	2 x 10.0	14	26	6.4	13	Y	100
TAHCR 16.00N	cream	2 x 5	2 x 16.0	14	30	8.2	18.4	Y	50
TAHGR 16.00N	green	2 x 5	2 x 16.0	14	30	8.2	18.4	Y	50
TAHB 16.00N	blue	2 x 5	2 x 16.0	14	30	8.2	18.4	Y	50

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.