

COLOURED PVC SLEEVINGS

Key features

- High-grade thin wall PVC sleeving ideal for insulating wire in areas where space is at a premium
- Supplied in continuous 100m coils
- Some sizes are available supplied on reels, please contact us for more information

Specification

Material:	PVC
Colours available:	Black, blue, brown, green, grey, red, white, yellow
Operating temperature:	-20°C to +70°C
Insulation resistance:	1010 Ohm/cm
Dielectric strength:	20 kV/mm
Elongation at break:	220%
Tensile strength:	15MPa
Hardness:	BSS20-30
Flammability:	Self Extinguishing in 30 seconds
Approvals:	BS 2848/3/85T, RoHS compliant



Part number	Internal dia. (mm)	To cover cable size (mm ²)	Coil length (m)	MOQ (Min order qty)
CY1.0 (Colour)	1.0	-	100	1
CY1.5 (Colour)	1.5	-	100	1
CY2.0 (Colour)	2.0	-	100	1
CY3.0 (Colour)	3.0	0.5 - 0.75	100	1
CY4.0 (Colour)	4.0	1.5 - 2.5	100	1
CY5.0 (Colour)	5.0	2.5 - 4.0	100	1
CY6.0 (Colour)	6.0	6.0	100	1
CY8.0 (Colour)	8.0	10.0	100	1
CY10.0 (Colour)	10.0	16.0 - 25.0	100	1
CY12.0 (Colour)	12.0	35.0	100	1
CY15.0 (Colour)	15.0	50.0	100	500

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.