

COLD SHRINK EPDM TUBE

DMC

- Manufactured from EPDM rubber
- Offering good mechanical, insulation and sealing protection
- Accommodating a wide range of cable sizes
- For indoor or outdoor applications
- Simple and fast installation



Selection Table

Cold Shrink Tube of General EPDM					
Product No.	Size	Application Range (mm/inch)	Length after Relaxed (mm/inch)	Material	Color
8320-6	Ø20	8~15/0.30~0.59	50~550/2~22	EPDM Rubber	Black
8325-L	Ø25	10~20/0.39~0.79	50~550/2~22	EPDM Rubber	Black
8335-L	Ø35	14~30/0.55~1.18	50~550/2~22	EPDM Rubber	Black
8340-L	Ø40	17.5~33/0.69~1.30	50~550/2~22	EPDM Rubber	Black
8353-L	Ø53	25~46/0.98~1.81	50~550/2~22	EPDM Rubber	Black
8370-L	Ø70	32~63/1.26~2.48	50~470/2~18	EPDM Rubber	Black
8104-9	Ø104	43~94/1.69~3.70	50~470/2~18	EPDM Rubber	Black
8125-9	Ø125	46~114/1.81~4.49	50~470/2~18	EPDM Rubber	Black
8150-18	Ø150	55~135/2.17~5.31	50~470/2~18	EPDM Rubber	Black

Cold Shrink Tube of High Shrinkage Ratio EPDM					
Product No.	Size	Application Range (mm/inch)	Length after Relaxed (mm/inch)	Material	Color
8432-L	Ø32	12~28/0.47~1.10	50~550/2~22	EPDM Rubber	Black
8435-L	Ø35	12.5~30/0.49~1.18	50~550/2~22	EPDM Rubber	Black
8440-L	Ø40	14~33/0.55~1.30	50~550/2~22	EPDM Rubber	Black
8453-L	Ø53	19~46/0.75~1.81	50~550/2~22	EPDM Rubber	Black
8460-10	Ø60	20.5~51/0.81~2.01	50~470/2~18	EPDM Rubber	Black
8470-L	Ø70	25~63/0.98~2.48	50~470/2~18	EPDM Rubber	Black
8480-13	Ø80	27.4~70/1.08~2.75	50~470/2~18	EPDM Rubber	Black

Remark: L indicates the required length after relaxed with the unit of mm or inch.

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.