

NORMOTO SBF1800 SERIES

- Housing material PA 6.6 GF25
- Blade material copper, tin plated
- Application specific, EU developed melting wire
- Suitable for use in low voltage applications up to 80V DC
- Breaking capacity 1000A at 80V DC
- Color coded body materials, rating marked on top using OCR font
- Check fuse in fuse block using test points at top of the fuse
- Blade rigidity through robust/sturdy body construction



PRT NR.	COLOR	TAB	B	H	RATING A	RATING V	MOQ
SBF1801P	black	5.2	19.0	20.0	1	80	100
SBF1802P	grey	5.2	19.0	20.0	2	80	100
SBF1803	violet	5.2	19.0	20.0	3	80	100
SBF1804	pink	5.2	19.0	20.0	4	80	100
SBF1805	tan	5.2	19.0	20.0	5	80	100
SBF1875	brown	5.2	19.0	20.0	7.5	80	100
SBF1810	red	5.2	19.0	20.0	10	80	100
SBF1815	blue	5.2	19.0	20.0	15	80	100
SBF1820	yellow	5.2	19.0	20.0	20	80	100
SBF1825	natural	5.2	19.0	20.0	25	80	100
SBF1830	green	5.2	19.0	20.0	30	80	100
SBF1840	orange	5.2	19.0	20.0	40	80	100



We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.