

## BRASS JACOB ADAPTERS, METRIC TO PG

Material Brass CuZn39Pb3, nickel-plated  
External thread Metric (EN 60423)  
Internal thread PG (DIN 40430)  
Temperature range -60 °C up to +200 °C



Typenr.	Connecting thread from - to	Thread length (mm)	Height (mm)	Packing (pcs)
M12-PG7 brass adapter	M12 x 1,5 - PG7	6,0	16,0	100
M12-PG9 brass adapter	M12 x 1,5 - PG9	6,0	16,5	100
M16-PG11 brass adapter	M16 x 1,5 - PG11	6,0	17,0	100
M20-PG11 brass adapter	M20 x 1,5 - PG11	6,5	17,5	100
M20-PG13,5 brass adapter	M20 x 1,5 - PG13,5	6,5	19,0	100
M25-PG16 brass adapter	M25 x 1,5 - PG16	7,0	20,5	50
M25-PG21 brass adapter	M25 x 1,5 - PG21	7,0	22,0	50
M32-PG29 brass adapter	M32 x 1,5 - PG29	8,0	24,5	25
M40-PG29 brass adapter	M40 x 1,5 - PG29	8,0	24,5	25
M50-PG36 brass adapter	M50 x 1,5 - PG36	9,0	28,5	10
M50-PG42 brass adapter	M50 x 1,5 - PG42	9,0	31,0	5
M63-PG48 brass adapter	M63 x 1,5 - PG48	10,0	33,0	5

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request).  
For this, we refer you to the website of Jacob GmbH: [www.jacob-gmbh.de/en/](http://www.jacob-gmbh.de/en/)