

BRASS JACOB CABLE GLANDS, PG

Material	Brass CuZn39Pb3, nickel-plated
Connecting thread	PG (DIN 40430)
Temperature range	-20 °C up to +100 °C
Protection grade	IP68 – 5 bar
Miscellaneous	Up to & including PG29, also available in a thread length of 15,0 mm From PG36 available with O-ring



Typenr.	Connecting thread	Cable diameter (mm)	Thread length (mm)	Packing (pcs)
PG7 brass cable gland	PG7	3,0 - 6,5	5,0	100
PG9 brass cable gland	PG9	4,0 - 8,0	6,0	100
PG11 brass cable gland	PG11	5,0 - 10,0	6,0	50
PG13,5 brass cable gland	PG13,5	6,0 - 12,0	6,5	50
PG16 brass cable gland	PG16	10,0 - 14,0	6,5	50
PG21 brass cable gland	PG21	13,0 - 18,0	7,0	50
PG29 brass cable gland	PG29	18,0 - 25,0	8,0	25
PG36 brass cable gland	PG36	24,0 - 32,0	9,0	10
PG42 brass cable gland	PG42	30,0 - 38,0	10,0	5
PG48 brass cable gland	PG48	34,0 - 44,0	10,0	5

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request).
For this, we refer you to the website of Jacob GmbH: www.jacob-gmbh.de/en/