

BRASS JACOB REDUCTIONS, PG

| | |
|-------------------|--|
| Material | Brass CuZn39Pb3, nickel-plated |
| Connecting thread | PG (DIN 40430) |
| Temperature range | -60 °C up to +200 °C |
| Protection grade | Dependent on the combination with other components |



| Typenr. | Connecting thread from - to | Thread length (mm) | Height (mm) | Packing (pcs) |
|-----------------------------|-----------------------------|--------------------|-------------|---------------|
| PG9-PG7 brass reduction | PG9 - PG7 | 6,0 | 8,5 | 100 |
| PG11-PG7 brass reduction | PG11 - PG7 | 6,0 | 8,5 | 100 |
| PG11-PG9 brass reduction | PG11 - PG9 | 6,0 | 8,5 | 100 |
| PG13,5-PG7 brass reduction | PG13,5 - PG7 | 6,5 | 9,0 | 100 |
| PG13,5-PG9 brass reduction | PG13,5 - PG9 | 6,5 | 9,0 | 100 |
| PG13,5-PG11 brass reduction | PG13,5 - PG11 | 6,5 | 9,0 | 100 |
| PG16-PG7 brass reduction | PG16 - PG7 | 6,5 | 9,5 | 100 |
| PG16-PG9 brass reduction | PG16 - PG9 | 6,5 | 9,5 | 100 |
| PG16-PG11 brass reduction | PG16 - PG11 | 6,5 | 9,5 | 100 |
| PG16-PG13,5 brass reduction | PG16 - PG13,5 | 6,5 | 9,5 | 100 |
| PG21-PG11 brass reduction | PG21 - PG11 | 7,0 | 10,0 | 100 |
| PG21-PG13,5 brass reduction | PG21 - PG13,5 | 7,0 | 10,0 | 100 |
| PG21-PG16 brass reduction | PG21 - PG16 | 7,0 | 10,0 | 100 |
| PG29-PG16 brass reduction | PG29 - PG16 | 8,0 | 11,5 | 50 |
| PG29-PG21 brass reduction | PG29 - PG21 | 8,0 | 11,5 | 50 |
| PG36-PG21 brass reduction | PG36 - PG21 | 9,0 | 12,5 | 25 |
| PG36-PG29 brass reduction | PG36 - PG29 | 9,0 | 12,5 | 25 |
| PG42-PG29 brass reduction | PG42 - PG29 | 10,0 | 14,0 | 10 |
| PG42-PG36 brass reduction | PG42 - PG36 | 10,0 | 14,0 | 10 |
| PG48-PG36 brass reduction | PG48 - PG36 | 10,0 | 14,0 | 10 |
| PG48-PG42 brass reduction | PG48 - PG42 | 10,0 | 14,0 | 10 |

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request).
For this, we refer you to the website of Jacob GmbH: www.jacob-gmbh.de/en/