

BRASS JACOB REDUCTIONS, METRIC

Material	Brass CuZn39Pb3, nickel-plated
Connecting thread	Metric (EN 60423)
Temperature range	-60 °C up to +200 °C
Protection grade	Dependent on the combination with other components



Typenr.	Connecting thread from - to	Thread length (mm)	Height (mm)	Packing (pcs)
M16-M12 brass reduction	M16 x 1,5 - M12 x 1,5	6,0	8,5	100
M20-M12 brass reduction	M20 x 1,5 - M12 x 1,5	6,5	9,0	100
M20-M16 brass reduction	M20 x 1,5 - M16 x 1,5	6,5	9,0	100
M25-M16 brass reduction	M25 x 1,5 - M16 x 1,5	7,0	10,0	100
M25-M20 brass reduction	M25 x 1,5 - M20 x 1,5	7,0	10,0	100
M32-M20 brass reduction	M32 x 1,5 - M20 x 1,5	8,0	11,5	50
M32-M25 brass reduction	M32 x 1,5 - M25 x 1,5	8,0	11,5	50
M40-M25 brass reduction	M40 x 1,5 - M25 x 1,5	9,0	12,5	25
M40-M32 brass reduction	M40 x 1,5 - M32 x 1,5	9,0	12,5	25
M50-M32 brass reduction	M50 x 1,5 - M32 x 1,5	10,0	14,0	10
M50-M40 brass reduction	M50 x 1,5 - M40 x 1,5	10,0	14,0	10
M63-M40 brass reduction	M63 x 1,5 - M40 x 1,5	10,0	14,0	10
M63-M50 brass reduction	M63 x 1,5 - M50 x 1,5	10,0	14,0	10

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request).
For this, we refer you to the website of Jacob GmbH: www.jacob-gmbh.de/en/