

CARTRIDGE FUSES J - JLP - JM - JMS

SERIES FEMALE SMALL

- Meets international specs, complies to ISO 8820-4, JASO D612 and other standards
- Element visibility from top through transparent cover
- Robust/sturdy body construction
- Self extinguishing, color coded body materials
- High temperature resistive plastics used for fuse body materials
- Secure and controlled time-delayed functioning with purpose designed elements
- Integrated, durable, Cu-alloy receptacles
- Used in Japanese, European, American and Korean designed vehicles



PRT NR.	COLOR	B	H	RATING A	RATING V	MOQ
CBF020J	blue	14.1	27.2	20	32	5
CBF025J	white	14.1	27.2	25	32	5
CBF030J	pink	14.1	27.2	30	32	5
CBF040J	green	14.1	27.2	40	32	5
CBF050J	red	14.1	27.2	50	32	5
CBF060J	yellow	14.1	27.2	60	32	5
CBF020JLP	blue	14.1	15.9	20	58	5
CBF025JLP	white	14.1	15.9	25	58	5
CBF030JLP	pink	14.1	15.9	30	58	5
CBF040JLP	green	14.1	15.9	40	58	5
CBF050JLP	red	14.1	15.9	50	58	5
CBF060JLP	yellow	14.1	15.9	60	58	5
CBF015JM	grey	10.7	15	15	32	5
CBF020JM	blue	10.7	15	20	32	5
CBF025JM	white	10.7	15	25	32	5
CBF030JM	pink	10.7	15	30	32	5
CBF040JM	green	10.7	15	40	32	5
CBF015JMS	grey	10.7	17.5	15	32	5
CBF020JMS	blue	10.7	17.5	20	32	5
CBF025JMS	white	10.7	17.5	25	32	5
CBF030JMS	pink	10.7	17.5	30	32	5
CBF040JMS	green	10.7	17.5	40	32	5
CBF050JMS	red	10.7	17.5	50	32	5
CBF060JMS	yellow	10.7	17.5	60	32	5

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.