

## EX BRASS JACOB ENLARGERS, METRIC

Material	Brass CuZn39Pb3, nickel-plated
Connecting thread	Metric (EN 60423)
Group (zone)	2G, 2D and 3G / 1, 2, 21, 22
Type of protection	Ex e, increased safety Ex tD A21 - Protection by enclosures
Temperature range	-30 °C up to +80 °C
Protection grade	IP68
Test standard	EN 60079-0 / EN 60079-7 EN 61241-0 / EN 61241-1
EC-type certificate	DMT 99 ATEX E016



Typenr.	Connecting thread from - to	Thread length (mm)	Height (mm)	Packing (pcs)
M12-M16 Ex brass enlarger	M12 x 1,5 - M16 x 1,5	5,0	16,0	100
M16-M20 Ex brass enlarger	M16 x 1,5 - M20 x 1,5	5,0	16,5	100
M20-M25 Ex brass enlarger	M20 x 1,5 - M25 x 1,5	6,0	18,5	50
M25-M32 Ex brass enlarger	M25 x 1,5 - M32 x 1,5	7,0	20,5	25
M32-M40 Ex brass enlarger	M32 x 1,5 - M40 x 1,5	8,0	23,5	25
M40-M50 Ex brass enlarger	M40 x 1,5 - M50 x 1,5	8,0	30,0	10
M50-M63 Ex brass enlarger	M50 x 1,5 - M63 x 1,5	9,0	32,5	10

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request). For this, we refer you to the website of Jacob GmbH: [www.jacob-gmbh.de/en/](http://www.jacob-gmbh.de/en/)