

## EX BRASS JACOB SCREW PLUGS, METRIC

Material	Brass CuZn39Pb3, nickel-plated
Connecting thread	Metric (EN 60423)
Group (zone)	2G, 2D and 3G / 1, 2, 21, 22
Type of protection	Ex e, increased safety Ex tD A21 - Protection by enclosures
Temperature range	-30 °C up to +80 °C
Protection grade	IP68
Test standard	EN 60079-0 / EN 60079-7 EN 61241-0 / EN 61241-1
EC-type certificate	DMT 99 ATEX E016



Typenr.	Connecting thread	Ø (mm)	Thread length (mm)	Height (mm)	Packing (pcs)
M12 Ex brass screw plug	M12 x 1,5	16,0	5,0	8,0	100
M16 Ex brass screw plug	M16 x 1,5	20,0	6,0	9,0	100
M20 Ex brass screw plug	M20 x 1,5	24,0	6,5	9,5	100
M25 Ex brass screw plug	M25 x 1,5	28,0	7,0	11,0	100
M32 Ex brass screw plug	M32 x 1,5	35,0	8,0	12,0	50
M40 Ex brass screw plug	M40 x 1,5	45,0	8,0	12,0	50
M50 Ex brass screw plug	M50 x 1,5	55,0	9,0	15,0	25
M63 Ex brass screw plug	M63 x 1,5	68,0	10,0	16,0	10

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request).  
For this, we refer you to the website of Jacob GmbH: [www.jacob-gmbh.de/en/](http://www.jacob-gmbh.de/en/)