

POLYAMIDE PA6 GF30 JACOB ADAPTERS, METRIC TO PG

Material	Polyamide PA6 GF30
External thread	Metric (EN 60423)
Internal thread	PG (DIN 40430)
Temperature range	-30 °C up to +100 °C
Protection grade	Dependent on the combination with other components
Standard color	Light grey (RAL 7035)



Typenr.	Connecting thread from - to	Thread length (mm)	Height (mm)	Packing (pcs)
M12-PG7 PA6 GF30 adapter	M12 x 1,5 - PG7	8,0	21,0	100
M12-PG9 PA6 GF30 adapter	M12 x 1,5 - PG9	11,0	23,5	100
M16-PG9 PA6 GF30 adapter	M16 x 1,5 - PG9	11,0	24,5	100
M20-PG11 PA6 GF30 adapter	M20 x 1,5 - PG11	11,0	26,5	100
M20-PG13,5 PA6 GF30 adapter	M20 x 1,5 - PG13,5	11,0	26,0	100
M20-PG16 PA6 GF30 adapter	M20 x 1,5 - PG16	11,0	28,0	100
M25-PG16 PA6 GF30 adapter	M25 x 1,5 - PG16	11,0	29,0	50
M25-PG21 PA6 GF30 adapter	M25 x 1,5 - PG21	11,0	31,0	50
M32-PG21 PA6 GF30 adapter	M32 x 1,5 - PG21	10,0	25,0	25
M32-PG29 PA6 GF30 adapter	M32 x 1,5 - PG29	11,0	33,0	25
M40-PG29 PA6 GF30 adapter	M40 x 1,5 - PG29	11,0	34,0	10
M50-PG36 PA6 GF30 adapter	M50 x 1,5 - PG36	11,0	37,0	10
M50-PG42 PA6 GF30 adapter	M50 x 1,5 - PG42	11,0	39,0	10
M63-PG48 PA6 GF30 adapter	M63 x 1,5 - PG48	11,0	40,0	10

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request).
For this, we refer you to the website of Jacob GmbH: www.jacob-gmbh.de/en/