

POLYAMIDE PA6 GF30 JACOB ADAPTERS, PG TO METRIC

Material	Polyamide PA6 GF30
External thread	PG (DIN 40430)
Internal thread	Metric (EN 60423)
Temperature range	-30 °C up to +100 °C
Protection grade	Dependent on the combination with other components
Standard color	Light grey (RAL 7035)



Typenr.	Connecting thread from - to	Thread length (mm)	Height (mm)	Packing (pcs)
PG9-M12 PA6 GF30 adapter	PG9 - M12 x 1,5	8,0	20,0	100
PG9-M16 PA6 GF30 adapter	PG9 - M16 x 1,5	8,0	20,0	100
PG9-M20 PA6 GF30 adapter	PG9 - M20 x 1,5	8,0	20,0	100
PG11-M16 PA6 GF30 adapter	PG11 - M16 x 1,5	8,0	20,0	100
PG11-M20 PA6 GF30 adapter	PG11 - M20 x 1,5	8,0	20,0	100
PG13,5-M16 PA6 GF30 adapter	PG13,5 - M16 x 1,5	9,0	21,0	100
PG13,5-M20 PA6 GF30 adapter	PG13,5 - M20 x 1,5	9,0	21,0	100
PG13,5-M25 PA6 GF30 adapter	PG13,5 - M25 x 1,5	9,0	21,5	100
PG16-M20 PA6 GF30 adapter	PG16 - M20 x 1,5	10,0	22,0	100
PG16-M25 PA6 GF30 adapter	PG16 - M25 x 1,5	10,0	22,5	50
PG21-M25 PA6 GF30 adapter	PG21 - M25 x 1,5	11,0	23,5	50
PG21-M32 PA6 GF30 adapter	PG21 - M32 x 1,5	11,0	25,5	50
PG29-M32 PA6 GF30 adapter	PG29 - M32 x 1,5	11,0	25,5	50
PG29-M40 PA6 GF30 adapter	PG29 - M40 x 1,5	11,0	25,5	50

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request).
For this, we refer you to the website of Jacob GmbH: www.jacob-gmbh.de/en/