

POLYAMIDE PA6 GF30 JACOB SCREW PLUGS, METRIC

Material	Polyamide PA6 GF30
Connecting thread	Metric (EN 60423)
Temperature range	-40 °C up to +100 °C
Protection grade	IP54 IP66 / IP68 possible when using an additionally mounted sealing ring
Standard colors	Silver grey (RAL 7001), light grey (RAL 7035), black (RAL 9005)



Typenr.	Connecting thread	Ø (mm)	Thread length (mm)	Height (mm)	Packing (pcs)
M12 PA6 GF30 screw plug	M12 x 1,5	15,0	6,0	10,0	100
M16 PA6 GF30 screw plug	M16 x 1,5	20,0	6,0	10,5	100
M20 PA6 GF30 screw plug	M20 x 1,5	24,0	6,0	10,5	100
M25 PA6 GF30 screw plug	M25 x 1,5	30,0	8,0	13,0	100
M32 PA6 GF30 screw plug	M32 x 1,5	37,0	8,0	13,5	100
M40 PA6 GF30 screw plug	M40 x 1,5	46,0	8,0	14,0	50
M50 PA6 GF30 screw plug	M50 x 1,5	56,0	10,0	16,5	50
M63 PA6 GF30 screw plug	M63 x 1,5	70,0	12,0	17,0	50

POLYAMIDE PA6 GF30 JACOB SCREW PLUGS, PG

Material	Polyamide PA6 GF30
Connecting thread	PG (DIN 40430)
Temperature range	-30 °C up to +100 °C
Protection grade	IP54
Standard color	: Light grey (RAL 7035)



Typenr.	Connecting thread	Ø (mm)	Thread length (mm)	Height (mm)	Packing (pcs)
PG7 PA6 GF30 screw plug	PG7	15,0	6,0	10,0	100
PG9 PA6 GF30 screw plug	PG9	19,0	6,0	10,0	100
PG11 PA6 GF30 screw plug	PG11	22,0	6,0	10,0	100
PG13,5 PA6 GF30 screw plug	PG13,5	25,0	6,0	10,0	100
PG16 PA6 GF30 screw plug	PG16	27,0	6,0	10,0	100
PG21 PA6 GF30 screw plug	PG21	33,0	8,0	12,5	100
PG29 PA6 GF30 screw plug	PG29	44,5	8,0	13,0	100
PG36 PA6 GF30 screw plug	PG36	55,5	10,0	15,0	50
PG42 PA6 GF30 screw plug	PG42	62,5	10,0	15,5	50
PG48 PA6 GF30 screw plug	PG48	69,5	12,0	17,0	50

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request).
For this, we refer you to the website of Jacob GmbH: www.jacob-gmbh.de/en/