

POLYAMIDE PA6 V-2 JACOB CABLE GLANDS WITH SPIRAL TOP, METRIC

Material	Polyamide PA6 V-2
Connecting thread	Metric (EN 60423)
Temperature range	-20 °C up to +100 °C
Protection grade	IP68 – 5 bar
Test standard	EN 62444 / UL 514B
UL / CSA-File	E140310
Standard colors	Silver grey (RAL 7001), light grey (RAL 7035), black (RAL 9005)



Typenr.	Connecting thread	Cable diameter (mm)	Thread length (mm)	Height (mm)	Packing (pcs)
M12 PA6 V-2 cable gland spiral top	M12 x 1,5	3,0 - 6,5	8,0	63,5	100
M16 PA6 V-2 cable gland spiral top	M16 x 1,5	5,0 - 10,0	15,0	94,5	100
M20 PA6 V-2 cable gland spiral top	M20 x 1,5	6,0 - 12,0	11,0	101,5	50
M20-1 PA6 V-2 cable gland spiral top	M20 x 1,5	10,0 - 14,0	15,0	116,0	25
M25 PA6 V-2 cable gland spiral top	M25 x 1,5	13,0 - 18,0	15,0	132,5	25

POLYAMIDE PA6 V-2 JACOB CABLE GLANDS WITH SPIRAL TOP, PG

Material	Polyamide PA6 V-2
Connecting thread	PG (DIN 40430)
Temperature range	-20 °C up to +100 °C
Protection grade	IP68 – 5 bar
Test standard	UL 514B
UL / CSA-File	E140310
Standard colors	Silver grey (RAL 7001), light grey (RAL 7035), black (RAL 9005)



Typenr.	Connecting thread	Cable diameter (mm)	Thread length (mm)	Height (mm)	Packing (pcs)
PG7 PA6 V-2 cable gland spiral top	PG7	3,0 - 6,5	8,0	63,0	100
PG9 PA6 V-2 cable gland spiral top	PG9	4,0 - 8,0	8,0	74,0	100
PG11 PA6 V-2 cable gland spiral top	PG11	5,0 - 10,0	8,0	87,0	100
PG13,5 PA6 V-2 cable gland spiral top	PG13,5	6,0 - 12,0	9,0	98,0	50
PG16 PA6 V-2 cable gland spiral top	PG16	10,0 - 14,0	10,0	112,0	25
PG21 PA6 V-2 cable gland spiral top	PG21	13,0 - 18,0	11,0	130,0	25

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request).
For this, we refer you to the website of Jacob GmbH: www.jacob-gmbh.de/en/