

Material

Connecting thread

Water entry pressure

Temperature range

Protection grade

Typical air flow

## VENTING ELEMENTS

## STAINLESS STEEL JACOB VENTING ELEMENTS, METRIC

Stainless steel 1.4305 Metric (EN 60423)

> 400 ml / min / cm2 at p = 0,07 bar ≥ 0,83 bar (dynamic WEP, 30 seconds)

-40 °C up to +100 °C

IP66 / IP68 - 0,6 bar (60 min.) / IP69

Properties Protection for hermetically sealed electro-technical and electronic enclosures against condensation water from

alternating temperature and pressure

Continuous ventilation and adaption of the inner pressure

Hydrophobic and oleophobic PES-membrane





## Connecting thread short length

Typenr.	Connecting thread	Thread length (mm)	Height (mm)	Packing (pcs)
M12 stainless steel venting element short length	M12 x 1,5	6,0	13,0	25
M20 stainless steel venting element short length	M20 x 1,5	6,0	13,0	10
M40 stainless steel venting element short length	M40 x 1,5	8,0	18,0	5

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request).

For this, we refer you to the website of Jacob GmbH: www.jacob-gmbh.de/en/