

MINI SERIES MANUAL RESET

Features

ABSOLUTE BREAKING CAPACITY:	2000A@26Vdc
INTERRUPT RATING:	150A@14Vdc (for 5-10A) 225A@14Vdc (for 15A) 300A@14Vdc (for 20A) 450A@14Vdc (for 25-30A)
OPERATING TEMPERATURE:	-40° ~ 85° C
STORAGE TEMPERATURE:	-40° ~ 125° C

- Plastic cover with color code
- Compatible with mini fuse holders
- Meets SAE J553, ISO 10924-3

Manual reset

Once the breaker detects overload or short circuit conditions, it will trip to disconnect the circuit. If you want to reset the circuit, you need to push the reset button.



PRT NR.	COLOR	RATING A	RATING V
ACBMN0528V3	tan	5	28
ACBMN7528V3	brown	7,5	28
ACBMN1028V3	red	10	28
ACBMN1528V3	blue	15	28
ACBMN2028V3	yellow	20	28
ACBMN2528V3	natural	25	28
ACBMN3028V3	green	30	28

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.