

MEGAOTO OBFMG SERIES

- Meets international specs, complies to ISO 8820-5, JASO D612 and other standards
- Fusing element with diffusion tin droplet technology
- Element visibility, windows on both sides
- Thermoplastic, heat resistant, color coded housing
- M8 connection holes, spaced 51 mm
- Rating indication in OCR font, both sides
- Breaking capacity of 2000A at 32VDC
- Maximum torque 12Nm ± 1 Nm



PRT NR.	COLOR	RATING A	RATING V	SCREW
OBFMG080	red	80	32	M8
OBFMG100	yellow	100	32	M8
OBFMG125	green	125	32	M8
OBFMG150	orange	150	32	M8
OBFMG175	white	175	32	M8
OBFMG200	blue	200	32	M8
OBFMG225	tan	225	32	M8
OBFMG250	pink	250	32	M8
OBFMG300	grey	300	32	M8
OBFMG350	darkgreen	350	32	M8
OBFMG400	purple	400	32	M8
OBFMG450	darkyellow	450	32	M8
OBFMG500	brown	500	32	M8

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.