

MIDIOTO OBFMD SERIES

- Meets international specs, complies to ISO 8820-5, JASO D612 and other standards
- Element visibility through viewing window
- PA6T housing, heat & chemical resistant
- Rigid Sn-plated copper alloy blades
- Color coded housing, marked with amperage rating
- M5 connection holes for 30A - 125A, spaced 30 mm
- M6 connection holes for 30A - 200A, spaced 30 mm
- Maximum torque 4.5Nm ± 1 Nm



PRT NR.	COLOR	RATING A	RATING V	SCREW
OBFMD050	red	50	58	M5
OBFMD060	yellow	60	58	M5
OBFMD070	brown	70	58	M5
OBFMD080	white	80	58	M5
OBFMD100	blue	100	58	M5
OBFMD125	pink	125	58	M5
OBFMD030M6	orange	30	58	M6
OBFMD040M6	green	40	58	M6
OBFMD050M6	red	50	58	M6
OBFMD060M6	yellow	60	58	M6
OBFMD070M6	brown	70	58	M6
OBFMD080M6	white	80	58	M6
OBFMD100M6	blue	100	58	M6
OBFMD125M6	pink	125	58	M6
OBFMD150	grey	150	58	M6
OBFMD175	tan	175	58	M6
OBFMD200	violet	200	58	M6

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.