


TERMINALS

NYLON HALF-INSULATED FEMALE DISCONNECTORS STANDARD

Maximum electrical rating : 300 Volts.
Maximum temperature : 105 °C
Material : Brass
Plating : Electro tin plated
Insulation : Nylon

RoHS compliantt

Halogen free



PRT NR.	WIRE RANGE (MM ²)	COLOR	TAB SIZE	B	F	L	E	D	D1	UL	PACKED
EFNDF 1.25-110A5	0.5~1.5	red	2.8x0.5	3.2	6.5	19.0	10.7	3.9	1.7		10 x 100
EFNDF 1.25-110A8	0.5~1.5	red	2.8x0.8	3.2	6.5	19.0	10.7	3.9	1.7		10 x 100
EFNDF 1.25-187A5	0.5~1.5	red	4.8x0.8	5.0	6.4	19.2	10.7	3.9	1.7		10 x 100
EFNDF 1.25-187A8	0.5~1.5	red	4.8x0.8	5.0	6.4	19.2	10.7	3.9	1.7		10 x 100
EFNDF 1.25-250A	0.5~1.5	red	6.3x0.8	6.6	7.2	20.8	10.7	3.9	1.7		10 x 100
EFNDF 2-110A5	1.5~2.5	blue	2.8x0.5	3.2	6.5	19.0	10.7	4.5	2.3		10 x 100
EFNDF 2-110A8	1.5~2.5	blue	2.8x0.8	3.2	6.5	19.0	10.7	4.5	2.3		10 x 100
EFNDF 2-187A5	1.5~2.5	blue	4.8x0.5	5.0	6.4	19.2	10.7	4.5	2.3		10 x 100
EFNDF 2-187A8	1.5~2.5	blue	4.8x0.8	5.0	6.4	19.2	10.7	4.5	2.3		10 x 100
EFNDF 2-250A	1.5~2.5	blue	6.3x0.8	6.6	7.2	20.8	10.7	4.5	2.3		10 x 100
EFNDF 2-312A	1.5~2.5	blue	8.0x0.8	8.2	10.2	24.5	10.7	4.5	2.3		10 x 100
EFNDF 5.5-250A	4~6	yellow	6.3x0.8	6.6	7.2	23.8	12.0	6.4	3.4		10 x 100
EFNDF 5.5-375A	4~6	yellow	9.4x1.2	9.8	12.0	28.6	12.0	6.4	3.4		10 x 100

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.