

TERMINALS

NYLON INSULATED SPADE TERMINALS DIN 46237 BRAZED SEAM

All our connectors and terminals are electro tin plated because the soft character and corrosion durability of the tin coating result in low and stable contact resistance. Our tin coatings have a good resistance to oxidation in moderately corrosive environments.

Along with all benefits of basic insulation, the nylon insulation on our products offers an even higher resistance against heat and minimizes the whitening of the insulation after crimping. These characteristics make them suitable for even the toughest environments.

RoHS compliant

Halogen free



PRT NR.	WIRE RANGE (MM ²)	COLOR	D2	B	F	L	E	D	D1	UL	PACKED
EFN 1.25-B3ADINBS	0.5~1.5	red	3.2	6.0	5.3	19.3	10.7	3.9	1.7	Y	10 x 100
EFN 1.25-YS3ADINBS	0.5~1.5	red	3.7	6.0	5.3	19.3	10.7	3.9	1.7	Y	10 x 100
EFN 1.25-YS4ADINBS	0.5~1.5	red	4.3	8.0	6.3	21.3	10.7	3.9	1.7	Y	10 x 100
EFN 1.25-5ADINBS	0.5~1.5	red	5.3	10.0	7.3	23.3	10.7	3.9	1.7	Y	10 x 100
EFN 1.25-6ADINBS	0.5~1.5	red	6.5	11.0	9.3	25.9	10.7	3.9	1.7	Y	10 x 100
EFN 2-B3ADINBS	1.5~2.5	blue	3.2	6.0	6.3	19.6	10.7	4.5	2.3	Y	10 x 100
EFN 2-YS3ADINBS	1.5~2.5	blue	3.7	6.0	5.3	19.6	10.7	4.5	2.3	Y	10 x 100
EFN 2-YS4ADINBS	1.5~2.5	blue	4.3	8.0	6.3	21.6	10.7	4.5	2.3	Y	10 x 100
EFN 2-5ADINBS	1.5~2.5	blue	5.3	10.0	8.3	24.6	10.7	4.5	2.3	Y	10 x 100
EFN 2-6ADINBS	1.5~2.5	blue	6.5	11.0	10.3	27.1	10.7	4.5	2.3	Y	10 x 100
EFN 5.5-S4ADINBS	4~6	yellow	4.3	8.0	8.3	23.9	12.7	6.4	3.4	Y	10 x 100
EFN 5.5-5ADINBS	4~6	yellow	5.3	10.0	9.3	26.1	12.7	6.4	3.4	Y	10 x 100
EFN 5.5-6ADINBS	4~6	yellow	6.5	11.0	10.5	27.9	12.7	6.4	3.4	Y	10 x 100
EFN 5.5-8ADINBS	4~6	yellow	8.4	14.0	13.3	32.3	12.7	6.4	3.4	Y	10 x 100

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.