


TERMINALS

PVC Insulated Pin Terminals Strait Copper Sleeve

Maximum electrical rating : 600 Volts.
 Maximum temperature : 75 °C
 Material : Copper
 Plating : Electro tin plated
 Insulation : PVC



RoHS compliant

PRT NR.	WIRE RANGE (MM ²)	COLOR	B	F	L	E	D	D1	RATING A	RATING V	UL	PACKED
RBFVDPC 1.25-F9	0.5~1.5	red	1.9	9.0	18.8	10.0	4.3	1.7	19A	600V		10 x 100
RBFVDPC 1.25-F10	0.5~1.5	red	1.9	10.0	19.8	10.0	4.3	1.7	19A	600V		10 x 100
RBFVDPC 1.25	0.5~1.5	red	1.9	12.0	21.8	10.0	4.3	1.7	19A	600V		10 x 100
RBFVDPC 2-F9	1.5~2.5	blue	1.9	9.0	18.8	10.0	4.8	2.3	27A	600V		10 x 100
RBFVDPC 2-F10	1.5~2.5	blue	1.9	10.0	19.8	10.0	4.8	2.3	27A	600V		10 x 100
RBFVDPC 2	1.5~2.5	blue	1.9	12.0	21.8	10.0	4.8	2.3	27A	600V		10 x 100
RBFVDPC 2-F13	1.5~2.5	blue	1.9	13.0	22.8	10.0	4.8	2.3	27A	600V		10 x 100
RBFVDPC 5.5	4~6	yellow	2.8	14.0	26.0	13.0	6.7	3.4	48A	600V		10 x 100

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.