


TERMINALS

PVC FULLY-INSULATED DISCONNECTORS STANDARD

Maximum electrical rating : 300 Volts.
 Maximum temperature : 75 °C
 Material : Brass
 Plating : Electro tin plated
 Insulation : PVC



RoHS compliant

PRT NR.	WIRE RANGE (MM ²)	COLOR	TAB SIZE	B	F	L	E	D	D1	UL	PACKED
RBLVDF 1.25-110A5	0.5~1.5	red	2.8x0.5	3.2	6.5	19.0	10.5	3.5	1.7		10 x 100
RBLVDF 1.25-110A8	0.5~1.5	red	2.8x0.8	3.2	6.5	19.0	10.5	3.5	1.7		10 x 100
RBLVDF 1.25-187A5	0.5~1.5	red	4.8x0.5	5.0	6.4	19.0	10.5	3.5	1.7		10 x 100
RBLVDF 1.25-187A8	0.5~1.5	red	4.8x0.8	5.0	6.4	19.0	10.5	3.5	1.7		10 x 100
RBLVDF 1.25-250A SQUARE	0.5~1.5	red	6.3x0.8	6.6	7.2	22.8	10.5	3.5	1.7		10 x 100
RBLVDF 2-110A5	1.5~2.5	blue	2.8x0.5	3.2	6.5	19.0	10.5	4.3	2.3		10 x 100
RBLVDF 2-110A8	1.5~2.5	blue	2.8x0.8	3.2	6.5	19.0	10.5	4.3	2.3		10 x 100
RBLVDF 2-187A5	1.5~2.5	blue	4.8x0.5	5.0	6.4	21.8	10.5	4.3	2.3		10 x 100
RBLVDF 2-187A8	1.5~2.5	blue	4.8x0.8	5.0	6.4	21.8	10.5	4.3	2.3		10 x 100
RBLVDF 2-250A SQUARE	1.5~2.5	blue	6.3x0.8	6.6	7.2	22.0	10.5	4.3	2.3		10 x 100
RBLVDF 5.5-250A	4~6	yellow	6.3x0.8	6.6	7.2	23.8	10.9	5.6	3.4		10 x 100

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.