

TERMINALS

NYLON INSULATED BLADE TERMINALS

Maximum electrical rating : 600 Volts.
 Maximum temperature : 105 °C
 Material : Copper
 Plating : Electro tin plated
 Insulation : Nylon



ONLY AVAILABLE IN STANDARD VERSION

RoHS compliant

Halogen free

PRT NR.	WIRE RANGE (MM ²)	COLOR	B	F	L	E	D	D1	UL	PACKED
EFNPC 1.25-PF10	0.5~1.5	red	2.3	10.0	20.5	10.7	3.9	1.7	Y	10 x 100
EFNPC 1.25-PF11	0.5~1.5	red	3.0	11.0	21.5	10.7	3.9	1.7	Y	10 x 100
EFNPC 1.25-PF14	0.5~1.5	red	2.4	14.0	24.5	10.7	3.9	1.7	Y	10 x 100
EFNPC 1.25-P	0.5~1.5	red	2.2	18.0	28.5	10.7	3.9	1.7	Y	10 x 100
EFNPC 2-PF9	1.5~2.5	blue	2.8	9.0	19.5	10.7	4.5	2.3	Y	10 x 100
EFNPC 2-PF10	1.5~2.5	blue	2.3	10.0	20.5	10.7	4.5	2.3	Y	10 x 100
EFNPC 2-PF13	1.5~2.5	blue	2.4	13.0	23.5	10.7	4.5	2.3	Y	10 x 100
EFNPC 2-P	1.5~2.5	blue	2.2	18.0	28.5	10.7	4.5	2.3	Y	10 x 100
EFNPC 5.5-PF10	4~6	yellow	2.8	10.0	22.7	12.7	6.3	3.4	Y	10 x 100
EFNPC 5.5-P	4~6	yellow	4.5	18.0	30.7	12.7	6.3	3.4	Y	10 x 100

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.