

TERMINALS

NYLON TERMINAL BLOCKS

MATERIAL: PA 6.6 (nylon)
 INSERT: Brass
 SCREWS: Galvanized iron
 MIN. OPERATING TEMP: -35°C
 MAX. OPERATING TEMP: 120°C
 QUALITY ASSURANCE: CE/96/EC
 APPLICABLE STANDARD: EN60998-1: 2004 & EN60988-2-1: 2004



Flame retardant to UL 94 Class V-2
 Solvent resistant
 Good bounce impact force
 Available in black and white

| PRT NR. | WIRERANGE (MM ²) | COLOR | SCREW | A | B | C | D | D | D | D | RATING | PACKED |
|-----------|------------------------------|-------|-------|-------|------|------|------|------|------|------|-------------|--------|
| KSPA-3WH | 2,5~4,0 | white | M2,5 | 95.3 | 17.5 | 13 | 8 | 6 | 8 | 6 | 3A / 380V | 10 |
| KSPA-3BL | 2,5~4,0 | black | M2,5 | 95.3 | 17.5 | 13 | 8 | 6 | 8 | 6 | 3A / 380V | 10 |
| KSPA-4WH | 4,0~6,0 | white | M3,0 | 117.4 | 19 | 15.5 | 10 | 6.3 | 10 | 6.3 | 6A / 380V | 10 |
| KSPA-4BL | 4,0~6,0 | black | M3,0 | 117.4 | 19 | 15.5 | 10 | 6.3 | 10 | 6.3 | 6A / 380V | 10 |
| KSPA-5WH | 6,0~10,0 | white | M3,0 | 132.6 | 21.2 | 16.6 | 11 | 7 | 11 | 7 | 10A / 380V | 10 |
| KSPA-5BL | 6,0~10,0 | black | M3,0 | 132.6 | 21.2 | 16.6 | 11 | 7 | 11 | 7 | 10A / 380V | 10 |
| KSPA-6WH | 10,0~12,0 | white | M3,5 | 142 | 23.2 | 19 | 11.8 | 8.5 | 11.8 | 8.5 | 15A / 380V | 10 |
| KSPA-6BL | 10,0~12,0 | black | M3,5 | 142 | 23.2 | 19 | 11.8 | 8.5 | 11.8 | 8.5 | 15A / 380V | 10 |
| KSPA-8WH | 12,0~14,0 | white | M4,0 | 141.5 | 23.4 | 20.4 | 12.2 | 9.4 | 12.2 | 9.4 | 20A / 380V | 10 |
| KSPA-8BL | 12,0~14,0 | black | M4,0 | 141.5 | 23.4 | 20.4 | 12.2 | 9.4 | 12.2 | 9.4 | 20A / 380V | 10 |
| KSPA-9WH | 16 | white | M4,0 | 169 | 26.1 | 20.5 | 14.2 | 9.3 | 14.2 | 9.3 | 30A / 380V | 10 |
| KSPA-9BL | 16 | black | M4,0 | 169 | 26.1 | 20.5 | 14.2 | 9.3 | 14.2 | 9.3 | 30A / 380V | 10 |
| KSPA-10WH | 25 | white | M4,0 | 192 | 30 | 26 | 16.2 | 11 | 16.2 | 11 | 60A / 380V | 10 |
| KSPA-10BL | 25 | black | M4,0 | 192 | 30 | 26 | 16.2 | 11 | 16.2 | 11 | 60A / 380V | 10 |
| KSPA-12WH | 35 | white | M5,0 | 233.5 | 37 | 29.8 | 20 | 13.8 | 20 | 13.8 | 80A / 400V | 10 |
| KSPA-12BL | 35 | black | M5,0 | 233.5 | 37 | 29.8 | 20 | 13.8 | 20 | 13.8 | 80A / 400V | 10 |
| KSPA-15WH | 40 | white | M6,0 | 262 | 46.1 | 35.7 | 22.5 | 20.5 | 22.5 | 20.5 | 100A / 450V | 10 |
| KSPA-15BL | 40 | black | M6,0 | 262 | 46.1 | 35.7 | 22.5 | 20.5 | 22.5 | 20.5 | 100A / 450V | 10 |

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.