

TERMINALS

SOLDER BUTT CONNECTORS DUOFLUX

MATERIAL: Polyolefin tubing with thermoplastic, color coded, adhesive rings
 SHRINK RATIO: 3:1
 SOLDER PREFORM: With Flux
 OPERATING TEMP: -55 - 125°C
 MINIMUM SHRINK TEMP: 140°C
 VOLUME RESISTIVITY: < equal length of wire
 DIELECTRIC STRENGTH (KV/MM): 20
 VOLTAGE DROP: 2mV



For tin plate or bare copper stranded wires, rated for at least 85°C

PRT NR.	WIRE RANGE AWG	WIRE RANGE (MM ²)	COLOR	L	Ø A	Ø B MIN	Ø B MAX/Ø C MAX	Ø C MIN	UL	MOQ
DCWT-9002	21~17	0.4~1.0	red	31	2.3	1.5	2.3	1.8		1000
DCWT-9003	17~14	1.0~2.5	blue	36	4.3	2.0	4.3	2.3		1000
DCWT-9004	12~10	3~5	yellow	42	6.8	3.4	6.8	3.7		1000

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.