

TERMINALS
SOLDER BUTT CONNECTORS STEP DOWN

MATERIAL: Heat shrinkable polyolefin tubing with thermoplastic, color coded, adhesive rings
 SOLDER PREFORM: With Flux
 OPERATING TEMP: -55 - 125°C
 MINIMUM SHRINK TEMP: 85°C
 VOLUME RESISTIVITY (Ω/CM): ≥ 1015
 DIELECTRIC STRENGTH (KV/MM): ≥ 25
 VOLTAGE RESISTANT: 600V



PRT NR.	WIRE RANGE AWG	WIRE RANGE (MM ²)	COLOR CODE	L	Ø A	Ø B MIN	Ø B MAX/Ø C MAX	Ø C MIN	UL	MOQ
CWT-9003 SD-2	22~14	0.5~2.5	blue to red	40	4.5	1.3	4.5	1.2		1000
CWT-9003 SD	22~14	0.5~2.5	yellow to blue	40	4.5	1.3	4.5	1.2		1000

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.