

TERMINALS

NON-INSULATED BUTT CONNECTORS BC AND C SERIES

MAX. ELECTRICAL
MATERIAL:
PLATING:
INSULATION:

RATING: 600 Volts
Copper
Electro tin plated
None



RoHS compliant

PRT NR.	WIRE RANGE AWG	WIRE RANGE (MM ²)	L	A	C	UL	PACKED
BC 1.25	22~16	0.5~1.5	15	1.9	3.3		100
BC 2	16~14	1.5~2.5	15	2.3	4		100
BC 5.5	12~10	4~6	15	3.6	5.5		100
BC 5.5-F19	12~10	4~6	19	3.6	5.5		100
C 8	8	8	22.5	5.1	7.1		100
C 14	6	14	27.5	6.4	9		100
C 22	4	22	30.5	8.2	11.4		100
C 38	2	38	33.5	10.1	13.3		100
C 60	1/0	60	36	12	15.4		50
C 70	2/0	70	37.8	14	17.4		50
C 80	3/0	80	39.5	15.4	19.4		50
C 100	4/0	100	39.5	17.6	22		40
C 125	250 kcmil	125	43.4	19.2	24.1		25
C 150	250/300 kcmil	150	55.5	20.9	26		5
C 180	300/350 kcmil	180	58.5	22	28.6		5
C 200	400 kcmil	200	64.5	25.7	32.5		5
C 250	400/450 kcmil	250	64.5	25.7	32.5		5
C 325		325	73.5	29	37		5

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.