

TERMINALS
GEL-FILLED SPLICE CONNECTORS



PRT NR.	COLOR	WIRE RANGE AWG	WIRE RANGE MM ²	PRODUCT IMAGE	PRODUCT IMAGE	PRODUCT IMAGE	DESCRIPTION	W	L	H1	H2	PACKED
CL 510216	yellow	26~21	0.4~0.7				Polycarbonate two-wire connector for solid copper cable, max. outer Ø 1,52 mm	8.6	12.0	5.9	8.2	100
CL 510217	orange	26~19	0.4~0.9				Polypropylene two-wire connector for solid copper cable, max. outer Ø 2,08 mm	9.8	15.3	5.8	98.4	100
CL 510218	red	26~19	0.4~0.9				Polypropylene two- or three-wire connector for solid copper, air core or filled cable, max outer Ø 2,08 mm	12.3	17.2	5.8	8.2	100
CL 510219	green	26~19	0.4~0.9				Polycarbonate two-wire connector for solid copper, air core or filled cable, max. outer Ø 1,67 mm	2.0	12.8	6.0	8.4	100
CL 510220	blue	22~14	0.3~2.0				Nylon two- or three-wire connector for solid copper cable, max. outer Ø 4,0 mm	23,5	23,5	10,4	17,0	20
CL 510220	red	24~19	0.5~0.9				Polycarbonate four-wire (1 full pair) inline connector for solid copper cable, max. outer Ø 3,18 mm	16.4	50.7	9.7	13.0	10

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.