

TERMINALS

TERMINAL BLOCKS

MATERIAL:	PA 6.6 (nylon)
INSERT:	Brass
SCREWS:	Galvanized iron
MIN. OPERATING TEMP:	-35°C
MAX. OPERATING TEMP:	120°C
QUALITY ASSURANCE:	CE/96/EC
APPLICABLE STANDARD:	EN60998-1: 2004 & EN60988-2-1: 2004



Flame retardant to UL 94 Class V-2

Solvent resistant

Good bounce impact force

Available in black and white

PRT NR.	WIRERANGE (MM ²)	COLOR	SCREW	A	B	C	D	D	D	D	RATING	PACKED
KSPA-3WH	2,5~4,0	white	M2,5	95.3	17.5	13	8	6	8	6	3A / 380V	10
KSPA-3BL	2,5~4,0	black	M2,5	95.3	17.5	13	8	6	8	6	3A / 380V	10
KSPA-4WH	4,0~6,0	white	M3,0	117.4	19	15.5	10	6.3	10	6.3	6A / 380V	10
KSPA-4BL	4,0~6,0	black	M3,0	117.4	19	15.5	10	6.3	10	6.3	6A / 380V	10
KSPA-5WH	6,0~10,0	white	M3,0	132.6	21.2	16.6	11	7	11	7	10A / 380V	10
KSPA-5BL	6,0~10,0	black	M3,0	132.6	21.2	16.6	11	7	11	7	10A / 380V	10
KSPA-6WH	10,0~12,0	white	M3,5	142	23.2	19	11.8	8.5	11.8	8.5	15A / 380V	10
KSPA-6BL	10,0~12,0	black	M3,5	142	23.2	19	11.8	8.5	11.8	8.5	15A / 380V	10
KSPA-8WH	12,0~14,0	white	M4,0	141.5	23.4	20.4	12.2	9.4	12.2	9.4	20A / 380V	10
KSPA-8BL	12,0~14,0	black	M4,0	141.5	23.4	20.4	12.2	9.4	12.2	9.4	20A / 380V	10
KSPA-9WH	16	white	M4,0	169	26.1	20.5	14.2	9.3	14.2	9.3	30A / 380V	10
KSPA-9BL	16	black	M4,0	169	26.1	20.5	14.2	9.3	14.2	9.3	30A / 380V	10
KSPA-10WH	25	white	M4,0	192	30	26	16.2	11	16.2	11	60A / 380V	10
KSPA-10BL	25	black	M4,0	192	30	26	16.2	11	16.2	11	60A / 380V	10
KSPA-12WH	35	white	M5,0	233.5	37	29.8	20	13.8	20	13.8	80A / 400V	10
KSPA-12BL	35	black	M5,0	233.5	37	29.8	20	13.8	20	13.8	80A / 400V	10
KSPA-15WH	40	white	M6,0	262	46.1	35.7	22.5	20.5	22.5	20.5	100A / 450V	10
KSPA-15BL	40	black	M6,0	262	46.1	35.7	22.5	20.5	22.5	20.5	100A / 450V	10

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.