

## TERMINALS












### NON-INSULATED NATURAL OPEN BARREL TERMINALS ON STRIP

OPERATING TEMP: 10 °C~105 °C  
MATERIAL: Brass














PRT NR.	WIRE RANGE	PRODUCT IMAGE	TAB-SIZE/Ø	L	B	DIMPLE/LOCKING TAB	UL	MOQ
01-001-MS-ZA	0,5~1,0		6.3 x 0.8	28.0	15.8	dimple/locking tab	Y	6000
01-002-MS-ZA	1,0~2,5		6.3 x 0.8	28.0	15.8	dimple/locking tab	Y	5000
01-003-MS-ZA	2,5~6,0		6.3 x 0.8	28.0	15.8	dimple/locking tab	Y	3500
02-010-MS-ZA	0,5~1,0		2.8 x 0.5	14.4	3.8	dimple	Y	15000
02-011-MS-ZA	0,5~1,0		2.8 x 0.8	14.4	3.8	dimple	Y	15000
02-012-MS-ZA	0,5~1,0		4.8 x 0.5	15.5	5.7	dimple	Y	10000
02-013-MS-ZA	0,5~1,0		4.8 x 0.8	15.5	5.7	dimple	Y	10000
02-001-MS-ZA	0,5~1,0		6.3 x 0.8	19.0	7.6	dimple	Y	8000
02-002-MS-ZA	1,0~2,5		6.3 x 0.8	19.0	7.6	dimple	Y	7000

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.

PRT NR.	WIRE RANGE	PRODUCT IMAGE	TAB-SIZE/Ø	L	B	DIMPLE/LOCKING TAB	UL	MOQ
02-003-MS-ZA	2,5~6,0		6.3 x 0.8	19.0	7.6	dimple	Y	5000
02-005-MS-ZA	0,5~1,0		6.3 x 0.8	19.0	7.6	dimple/locking tab	Y	8000
02-007-MS-ZA	1,0~2,5		6.3 x 0.8	19.0	7.6	dimple/locking tab	Y	7000
02-009-MS-ZA	2,5~6,0		6.3 x 0.8	19.0	7.6	dimple/locking tab	Y	4000
07-001-MS-ZA	0,5~1,0		6.3x0.8	20.0	7.6	dimple		1500
07-002-MS-ZA	0,75~1,5		6.3x0.8	20.0	7.6	dimple		1500
10-001-MS-ZA	0,5~1,0		6.3 x 0.8	16.0	7.6	dimple	Y	5000
10-002-MS-ZA	1,0~2,5		6.3 x 0.8	15.5	7.6	dimple	Y	4000
03-002-MS-ZA	0,5~1,0		ø 4.3	22.0	9.5	-	Y	6000
03-003-MS-ZA	0,5~1,0		ø 5.3	22.0	9.5	-	Y	6000
03-004-MS-ZA	0,5~1,0		ø 6.4	22.0	9.5	-	Y	6000

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.

PRT NR.	WIRE RANGE	PRODUCT IMAGE	TAB-SIZE/Ø	L	B	DIMPLE/LOCKING TAB	UL	MOQ
03-005-MS-ZA	1,0~2,5		ø 3.2	22.0	8.0	-	Y	6000
03-006-MS-ZA	1,0~2,5		ø 4.3	22.0	9.5	-	Y	6000
03-007-MS-ZA	1,0~2,5		ø 5.3	22.0	9.5	-	Y	6000
03-008-MS-ZA	1,0~2,5		ø 6.4	22.0	9.5	-	Y	6000
03-009-MS-ZA	1,0~2,5		ø 8.5	28.0	14.0	-		2500
09-001-MS-ZA	0,5~0,75		-	6.0	-	-		40000
09-002-MS-ZA	0,75~2,0		-	6.8	-	-		40000
05-001-MS-ZA	0,5~2,0		ø 3.5	13.2	7.5	-		7500
05-002-MS-ZA	0,5~2,0		ø 4.0	17.5	8.8	-		7500
06-001-MS-ZA	0,5~2,0		ø 3.5	17.6	7.0	-		5000
06-002-MS-ZA	0,5~2,0		ø 4.0	17.4	6.5	-		5000

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.