

**TERMINALS**  
NON-INSULATED TIN PLATED QUICK CONNECTORS

OPERATING TEMP: 10 °C~105 °C  
MATERIAL: Copper\*  
PLATING: Electro tin plated



\*Except for items 50-001-MB-TA and 50-002-MB-TA (these are brass)

PRT NR.	PRODUCT IMAGE	STUD HOLE	L	B	DIMPLE/ANGLE	UL	
50-001-MB-TA			18.0	11.4	dimple	1000	
50-002-MB-TA			20.5	9.6	dimple	1000	
08-101-MB-TA		Ø 2.2	5.0	4.45	dimple/45°	1000	
08-001-MB-TA		Ø 4.2	8.5	8.0	dimple/45°	1000	
08-110-MB-TA		Ø 5.2	8.5	8.0	dimple/45°	1000	
08-002-MB-TA		Ø 4.2	11.5	10.0	dimple/2 x 45°	1000	
08-012-MB-TA		Ø 5.2	11.5	10.0	dimple/2 x 45°	1000	

*We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.*