



AFTE Micro Heat Shrink

AFTE heat shrink tubing is available in lengths of 1,22 mtr or on spools with production lengths.

The standard colour of AFTE heat shrink tubing is natural.

Key properties:

- Excellent electrical properties
- Excellent chemical resistance
- Smoothness
- High dielectric constant
- Durable
- Application temperature 340°C
- UV resistant



Type	ID before shrink mm	ID after max. shrink mm	Wall thickness after max. shrink mm
AFTE-0,5	0,508	0,203	0.051
AFTE-0,6	0,635	0,254	0.051
AFTE-0,7	0,762	0,305	0.051
AFTE-0,8	0,864	0,381	0.051
AFTE-0,9	0,965	0,457	0.051
AFTE-1,1	1,168	0,559	0.051
AFTE-1,2	1,270	0,686	0.051
AFTE-1,3	1,397	0,813	0.051
AFTE-1,5	1,524	0,991	0.051
AFTE-1,9	1,930	1,245	0.051
AFTE-2,3	2,362	1,549	0.051
AFTE-3,0	3,048	1,829	0.051
AFTE-3,8	3,810	2,261	0.051
AFTE-4,8	4,851	2,845	0.051
AFTE-6,0	6,096	3,581	0.064

*The above mentioned dimensions and tolerances are our standard.
Other dimensions and/or tolerances available on request*

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.