

TERMINALS
DURASEAL

INSULATION: Nylon, with adhesive liner
 SHRINK RATIO: Approximately 2:1
 MATERIAL: Copper
 PLATING: Electro tin plated
 OPERATING TEMP: -55 ~ 125 °C
 MIN. SHRINK TEMPERATURE: > 150 °C
 DIELECTRIC STRENGTH: 2500 Vac
 INSULATION RESISTANCE: 1000 MΩ at 100 Vdc
 WIRE PULLOUT: 11,3 kg (red), 22,7 kg (blue), 27,2 kg (yellow)



RoHS compliant
 UL, CUL and Lloyd's listed
 Waterproof
 Not flame retardant
 Protects splices from water, condensation, salt, and corrosion
 Provides strain relief
 Protects against vibration in rugged environments
 Solvent resistance: isopropyl alcohol, trichloroethylene, gasoline, battery acid, diesel fuel, motor oil, antifreeze, brake fluid, 5% salt water

PRT NR.	WIRE RANGE (MM ²)	COLOR	F	L	D	D1	UL
D406-0001	1.0~1.5	red	15.0	31.5	3.7	1.5	
D406-0002	1.5~2.5	blue	15.0	31.5	4.6	2.3	
D406-0003	4~6	yellow	15.0	37.5	6.5	3.5	

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.