











MAXIOTO FUSE HOLDER SPLASH WATERPROOF

- PA 6.6-GF30 heat resistant body
- UL 94 Class V-0 self extinguishing
- IP54 splash waterproof



PRT NR.	PRODUCT IMAGE	WIRERANGE MM ²	DESCRIPTION
FH93004.0			Holder for BF9000 series, 1 position, wire size 4,0~6,0 mm ² (complete set in plastic box)
FH9315-A			Holder for BF9000 series, 1 position, wire size 4,0~6,0 mm ² (10 complete sets in plastic bag)
FH93010.0			Holder for BF9000 series, 1 position, wire size 6,0~10,0 mm ² (complete set in plastic box)
FH9315-B			Holder for BF9000 series, 1 position, wire size 6,0~10,0 mm ² (10 complete sets in plastic bag)
FH9301			Body, 1 position, PA66-GF35, UL04-V0, black
FH9305			Cover with integrated NBR seal, 1 position, clear PC



We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.

PRT NR.	PRODUCT IMAGE	WIRERANGE MM ²	DESCRIPTION
CCS930FL			Contact 4,0~6,0 mm ² , nickel plated brass Use with blue seal
CCS931FL			Contact 6,0~10,0 mm ² , nickel plated brass Use with grey seal
S183548X			Blue seal for cable 4,0~6,0 mm ² , silicone, Ø 3,1 mm
S184862X			Grey seal for cable 6,0~10,0 mm ² , silicone, Ø 4,4 mm