

MEGAOTO OMGHV SERIES

- Meets international specs, complies to ISO 20934 and other standards
- Rigid tin plated copper blades
- Sturdy riveted thermoplastic color coded housing
- M8 connection holes, spaced 51 mm
- Rating indication in OCR font, both sides
- Breaking capacity of 2500A at 70VDC
- Maximum torque 12 Nm ± 1 Nm



PRT NR.	COLOR	RATING A	RATING V	SCREW
OMGHV080	red	80	70	M8
OMGHV100	yellow	100	70	M8
OMGHV125	green	125	70	M8
OMGHV150	orange	150	70	M8
OMGHV175	white	175	70	M8
OMGHV200	blue	200	70	M8
OMGHV225	tan	225	70	M8
OMGHV250	pink	250	70	M8
OMGHV300	grey	300	70	M8
OMGHV350	darkgreen	350	70	M8
OMGHV400	purple	400	70	M8
OMGHV450	darkyellow	450	70	M8
OMGHV500	brown	500	70	M8

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.