







CIRCUIT BREAKERS



PRT NR.	PRODUCT IMAGE	DESCRIPTION	RATING	CONTACTS	IP	REMARKS
STAS001		Circuit breaker Plastic housing	500A@12-24V peak, 100A@12-24V continuous	M8 screw contacts, copper Length 35,6 mm	IP43	Light duty with rubber cover. Key removable in Off-position
STAS002		Circuit breaker	800A@12V DC intermittent, 300A@12V DC continuous	M10 screw contacts, copper Length 14,7 mm		With 2 keys Key removable in Off- position
STAS003		Circuit breaker	800A@12V DC intermittent, 300A@12V DC continuous	M10 screw contacts, copper Length 14,7 mm		With waterproof rubber covers Key removable in Off- position
STAS004		Circuit breaker	800A@12V DC intermittent, 300A@12V DC continuous	M10 screw contacts, copper Length 24,2 mm		Key removable in Off-position
STAS005		Circuit breaker	800A@12V DC intermittent, 300A@12V DC continuous	M10 screw contacts, copper Length 24,2 mm		With waterproof rubber covers. Key removable in Off- position
STAS006		Circuit breaker Zinc housing	800A@12V DC intermittent, 300A@12V DC continuous	M10 screw contacts, copper Length 25 mm		Red T-handle not removable

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.

PRT NR.	PRODUCT IMAGE	DESCRIPTION	RATING	CONTACTS	IP	REMARKS
STAS007		Circuit breaker Zinc housing with white paint coating	800A@12V DC intermittent, 300A@12V DC continuous	M10 screw contacts, copper Length 25 mm		Red T-handle not removable
STAS008		Circuit breaker Zinc housing with white paint coating	800A@12V DC intermittent, 300A@12V DC continuous	M10 screw contacts, copper Length 32 mm		Red T-handle not removable
STAS009		Circuit breaker Zinc housing with white paint coating	800A@12V DC intermittent, 300A@12V DC continuous	M10 screw contacts, copper Length 32 mm		Black T-handle not removable
STAS010		Circuit breaker	100A@12-24V continuous	M10 screw contacts and 6.4 tab contacts Copper		With waterproof rubber covers Key removable in Off- position
STAS011		Circuit breaker	1500A@12V DC cranking, 450A@12V DC intermittent, 300A@12V DC continuous	M10 screw contacts, copper Length 31 mm	IP56	Heavy duty Dual circuit Ignition protected
STAS012		Circuit breaker	1500A@12V DC cranking, 450A@12V DC intermittent, 300A@12V DC continuous	M10 screw contacts, copper Length 31 mm	IP56	Heavy duty Dual circuit Ignition protected Removable key
KEY001		Plastic key for STAS001				

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.