


## Climatic Chambers with temperature and humidity (FDMC-810-TH Series)

		FDMC-810-TH-PRO Touch Screen Controller	FDMC-810-TH PID Constant Controller
<b>(1) Climatic Performance:</b>			
Temperature Range without Humidity	(S)	0 to +70°C	
	(B)	-25°C to +70°C	
Temperature uniformity		0.5 to 2.5±°C	
Temperature fluctuation		0.1 to 0.5±°C	
Average heating-up rate according to EN 60068-3-5		+2°C/Min	
Average cooling down rate according to EN 60068-3-5		-1°C/Min	
Temperature range with active humidity		+10°C to +70°C	
Humidity Range		10 to 98 %rH	
Humidity fluctuation depending on setpoint		≤ 3±%	
<b>(2) Dimensions and Weight:</b>			
External Dimensions	Width	1200 mm	
	Depth	868 mm	
	Height	1920 mm	
Internal Dimensions	Width	1090 mm	
	Depth	580 mm	
	Height	1257 mm	
Internal net volume		810 L	
Net weight (Empty)		195 Kg	
<b>(3) Doors and Shelves:</b>			
Number of doors		2	
Number of shelves	Standard	6	Maximum 10
Shelf Dimension	Width	460 mm	Depth 570 mm
Permitted load per rack		30 Kg (Optional 35 Kg)	
Shelf Type		Removable and height adjustable stainless-steel grid	

		FDMC-810-TH-PRO Touch Screen Controller	FDMC-810-TH PID Constant Controller
<b>(4) Controller:</b>			
Controller		Touch Screen <b>revoFACE</b> Fully programmable	Constant PID Controller <b>stillFACE</b>
<b>(5) Materials of Construction:</b>			
External materials		AISI 304 Stainless Steel	
Internal materials		AISI 304 Stainless Steel	
Insulation		CFC and HCFC free	
Shelves		Stainless-steel grid	
<b>(6) Safety:</b>			
Temperature		Class 2 independent adjustable temperature safety devices (DIN 12880)	
Alarms		Audio-Visual	
<b>(7) Other Technical Specifications:</b>			
Humidification system		Ultrasonic	
Water filter		Water softening filter and replaceable cartridge equipped	
Max Water hardness permitted		600 ppm CaCO <sub>3</sub>	
Water Inlet		Pressure 0.2 to 5 BAR; Temperature 10°C to 40°C; Pipe connection 3/4"	
Sound-pressure level		60 dB(A)	
Ventilation		Fan forced ventilation	
<b>(8) Electrical Data:</b>			
Voltage		220 / 240 VAC single phase	
Frequency		50 Hz	
Nominal power		2.2 kW 2.6 kW (For -25°C to +70°C models)	
Unit fuse		16A	

## Operation flowchart



\*<sup>1</sup> Operation Temperature Humidity Limits

### Main Options:

- Ethernet interface for remote connection
- Interface port RS485
- USB port
- Upgrade. 50 program 200 step for revoFACE
- Interior socket coverable universal 220-230 V
- Internal compartments lexan door
- Flooding system for EN1348-2007
- Relative humidity decreasing up to 2% at 20°C
- Humidity extension range below the 10°C
- Power supply 110 V 50-60 Hz
- CO2 Regulation System for EN 12390-10
- Cable Hole
- Double tempered glass door
- Swivel castors with chamber lock
- System of supply water tank 16 liters
- Reinforced stainless steel shelf