

Thermostatic Chambers (FDMT-1020-T Series)

		FDMT-1020-T-PRO Touch Screen Controller	FDMT-1020-T PID Constant Controller	
(1) Temperature Performance:				
Temperature Range	(S)	0 to +70°C		
	(B)	-25°C to +70°C		
Temperature uniformity depending on setpoint		0.5 to 2.5±°C		
Temperature fluctuation depending on setpoint		0.1 to 0.5±°C		
Average heating-up rate according to EN 60068-3-5		+2°C/Min		
Average cooling down rate according to EN 60068-3-5		-1°C/Min		
(2) Dimensions and Weight:				
External Dimensions	Width	1500 mm		
	Depth	700 mm		
	Height	2100 mm		
Internal Dimensions	Width	1340 mm		
	Depth	570 mm		
	Height	1350 mm		
Internal net volume		1020 L		
Net weight (Empty)		205 Kg		
(3) Doors and Shelves:				
Number of doors		2		
Number of shelves	Standard	6	Maximum	12
Shelf Dimension	Width	530 mm	Depth	550 mm
Permitted load per rack		30 Kg (Optional 35 Kg)		
Shelf Type		Removable and height adjustable stainless-steel grid		

		FDMT-1020-T-PRO Touch Screen Controller	FDMT-1020-T PID Constant Controller
(4) Controller:			
Controller		Touch Screen revoFACE Fully programmable	Constant PID Controller stillFACE
(5) Materials of Construction:			
External materials		White coated galvanized steel or full Stainless steel AISI 304	
Internal materials		AISI 304 Stainless Steel	
Insulation		CFC and HCFC free	
Shelves		Stainless-steel grid	
(6) Safety:			
Temperature		Class 2 independent adjustable temperature safety devices (DIN 12880)	
Alarms		Audio-Visual	
(7) Other Technical Specifications:			
Sound-pressure level		60 dB(A)	
Ventilation		Fan forced ventilation	
(8) Electrical Data:			
Voltage		220 / 240 VAC single phase	
Frequency		50 Hz	
Nominal power		2.3 kW 2.7 kW (For -25°C to +70°C models)	
Unit fuse		16A	

Main Options:

- Ethernet interface for remote connection
- Interface port RS485
- Upgrade. 50 program 200 step for revoFACE
- Interior socket coverable universal 220-230 V
- Internal compartments lexan door
- Flooding system for EN1348-2007
- Relative humidity decreasing up to 2% at 20°C
- Power supply 110 V 50-60 Hz
- CO2 Regulation System for EN 12390-10
- Cable Hole
- USB port
- Double tempered glass door
- Swivel castors with chamber lock
- Reinforced stainless steel shelf