

# COOLED INCUBATOR

# CI 1160 PRO




- **Structure** : upright type, realized in sheet steel epoxy coated white colour both in- and outside or in stainless steel 18/10 AISI 304 both in- and outside. All the internal corners are rounded to make easy any cleaning operations and the internal bottom is tray type to contain spills
  - **Insulation** : high density (40 Kg/m<sup>3</sup>) foamed-in-place polyurethane, with a thickness of 75 mm. CFC-free
  - **Feet** : Nr 4 made in stainless steel 18/10 AISI 304, adjustable in height for levelling
  - **Insulated doors** : Nr 2, hinged, side-by-side, made with the same material and insulation as the rest of the structure (sheet steel epoxy coated white colour or stainless steel 18/10 AISI 304 always both in- and outside). The doors are provided with a removable magnetic rubber gaskets in order to grant a perfect hermetic closing. The handles are flush-fitting type so do not increase the size of the refrigerator. The doors are also fitted with a spring loaded automatic closing devices for openings inferior 90° and special door switches that stop the internal ventilation at the door opening (to limit the air cold loss) and light the internal lighting at every opening
  - **Internal equipment** : Nr 6 (3 for each door) storage open wire shelves realized sheet steel with a strong plastic coating (rust-proof material). The shelves are mounted on special anti-tilt stainless steel slides that allows the shelf extraction and they can be easily removed and adjusted in height without the use of any tool. The special internal racking-system allows a great flexibility of the internal fitting with the possibility of interchange and combine both shelves and drawers (drawers optionally available)
- Shelf dimensions (W x D cm) : 53 x 55
  - Shelf loading capability (Kg) : 35 (with uniformly stored material)
  - **Internal lighting** : Nr 2 bulbs, mounted in the bottom part of the control panel (1 above each door), with automatic activation at every door opening through a special switch
  - **Control panel "PRO PID"** : located in the top part of the structure (above the door), it is microprocessor operating with soft-touchpads and LCD display, allowing the control of all the functions and working status of the refrigerator (including alarms). The control panel is battery operating in order to grant the functioning of the alarms even in case of power failure. The main functions of the control panel are :
    - Large (2 lines writings) LCD display, retro-illuminated white colour with black characters, indicating the appliance working status ( defrosting, alarm running, actual temperature, etc.)
    - Digital temperature adjusting and displaying with an accuracy of 0,1°C
    - Keyboard password protected with automatic locking, to avoid tampering from unauthorized persons
    - Back-up battery, with automatic recharging, granting till 48 hours autonomy for the control panel functioning in case of power failure
    - Visual and acoustic alarm signalling (with automatic resetting) for:
      - high and low temperature with limits programmable from the user
      - door ajar, delayed of 3 minutes to allow the standard operations
      - power failure
      - battery discharged
      - condenser dirty
      - anti-freezing evaporator

- sensors failure
- Muting facilities for the acoustic alarms, with continuous warning indication on the display
- Alarms memory (not deletable) for the last 30 alarm conditions, with the possibility of checking from the display, the alarm condition, when the alarm is started, when it is ended and which is the highest or lowest peak reached from the temperature (if applicable)
- Events memory with the possibility of checking from the display, door openings, relays status, etc.
- NTC sensors for accuracy of the temperature control
- NO/NC contact to remote the alarm signals
- RS 485
- **Cooling unit** : top mounted, with the condensing unit compounded by Nr 1 hermetic compressors and Nr 1 finned condenser, air cooled through a fan. Also, in the ceiling of the storage chamber, is mounted the finned evaporator with copper pipes, that is housed into a stainless steel cover that incorporate the fan. All the mounted components are industrial grade to grant the maximum reliability
- **Refrigerant** : R404a CFC-free
- **Defrosting** : completely automatic, thermostat controlled. The condensate water is automatically channelled into an heated tray, located under cabinet, for the automatic evaporation of the condensate water
- **Heating element** : chamber mounted, housed into a stainless steel cover that incorporate the fan (same as for the evaporator). The heating element is industrial grade to grant the maximum reliability
- **Refrigeration/Heating** : forced-air, through a fan, granting the maximum temperature uniformity and stability inside of the cabinet
- **Temperature range** : infinitely adjustable between +2°C / +50°C
- **Temperature uniformity into the chamber** :  $\pm 2^{\circ}\text{C}$
- **Temperature stability** :  $\pm 2^{\circ}\text{C}$
- **Voltage (V/ph/Hz)** : 220-230/1/50
- **Plug** : Schuko type
- **Breakers** : Nr 2 glass cartridge fuses with a rating of 10A, at protection of the appliance
- **Noise level (dB(A))** :  $\leq 52$
- **Gross capacity (litres)** : 1295
- **Net capacity (litres)** : 1160
- **Dimensions (W x D x H cm)** : 150 x 70 x 210
- **Net weight (Kg)** : 220
- **Packed dimensions (W x D x H cm)** : 158 x 98 x 224 (3,47 m<sup>3</sup>)
- **Gross weight (Kg)** : 250

# COOLED INCUBATOR

# CI 1160 PRO

## ACCESSORIES AVAILABLE



Extra wire shelf



Wire basket



Plastic partitions for drawers




Kit of castors




Temperature chart recorder



Data logger function with USB port




Cable port with cover




Different voltage



Extra stainless steel wire shelf



Stainless steel drawer




Front top for drawers



Safety door lock with key




Electronic temperature printer



Internal electrical socket



Glass door (instead of insulated door)



Wooden crate packing



Vers. July 13

\* The declared performances are referred at +38°C ambient temperature, relative humidity of 70% and without any internal thermal mass (empty cabinet).

\* Should it be necessary or useful without undermining any model essential features, technical and stylistic characteristics are subject to be changed without manufacturer's previous notice.

N-Wissen GmbH

info@lab-wissen.de;

Tel: +49 (0) 69 8900 4008;

Fax: +49 (0) 69 8900 4007

Ferdinand-Porsche-Str. 2, 63073 Offenbach - Germany