



Special applications: Centrifuges life sciences

DIGTOR 22 COL

N-Wissen GmbH
info@lab-wissen.de;
Tel: +49 (0) 69 8900 4008;
Fax: +49 (0) 69 8900 4007
Ferdinand-Porsche-Str. 2, 63073 Offenbach - Germany

Max. capacity: 4 x 60 ml.

Max. speed: 1.801 xg / 3.000 RPM

Essential tool for fat processing, where we can find the highest concentration of stem cells, for liposculpture techniques and reparative surgery.

Features

- Available rotors for tubes (check Digtor 22 accessories, pag. 52)
- TFT color touch screen, visible from more than 3 m.:**
 - Shows RPM and RCF, time, acceleration/deceleration values (PCBS) and unbalancing location system (ULS).
 - Speed programming in 10 RPM/ 10 xg steps
 - Real RCF values on screen based in accessories configuration.
 - Count up/down from "0" or at "set RPM/RCF" for test reproducibility.
 - Timer countdown/up from "0" or at "set RPM/ RCF" for reproducible tests.
 - Timer from 1 sec. to 99 hours programmable in 1 sec. steps and hold position.
 - PCBS: Progressive controlled acceleration and braking system up to 175 selectable ramps that prevents sample homogenization after separation.
 - ULS: Unbalancing location system indicating on the screen the number of the bucket which produces the unbalance switch off.
 - 40 programmable memories, with protection under password.
 - Several acoustic and visual messages warning the user the device situation.

Easy to use

- Microprocessor controlled. PC connection.
- Induction motor maintenance free (brushless).
- Rotors and adapters list on memory.
- Noise level: below 60 dB.
- Start, stop, open lid and short spin with adjustable speed buttons.



DIGTOR 22 COL

- Option of free/locked adjustment of RPM/ RCF along the run.
- Automatic open lid, programmable.
- Last values remain in memory.
- Automatic rotor recognition. Over-speed protection.

Safety

- Lid provided with security systems:
 - Automatic lid lock system, motorized with double lock.
 - Emergency lid-lock release.
 - Locking and protection against opening along the run.
 - Lid dropping protection.
 - Port in the lid for calibration and operation checking.
- Unbalance detection and switch off.
- Protection safety ring between the centrifugation chamber and the housing.
- Chamber of centrifugation in stainless steel (easy cleaning).
- Rotors and adapters autoclavable, easy to install by the user.
- Forced ventilation to reduce temperature increasing.
- Automatic disconnection for energy saving up to 8 h., with deactivation option.

EU Directives: 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU.

Standards: EN 61010-1, EN 61010-2-020, EN 61326-2-6, EN 61326-1.

Versions	Dimensions (mm)(w x d x h)			Net weight (Kg)	Voltage (V)	Frecuency (Hz)	Consumption (W)
CE 204	540	650	400	50	220-230	50-60	460
CE 205	540	650	400	50	110-120	50-60	460

Accessories

RT 210



ROTOR	SWING OUT		
Max. capacity	4x60 ml		
RPM Max.	3.000		
Radius (mm)	179		
RCF Max. (xg)	1.801		
SAMPLE VOLUME	Dim (mm) approx.	ADAPTERS	
Syringes 60 ml. / 10 ml.	31x165 / 16x118	Tubes 4 / 16	Ref. - / RE 438



N-Wissen GmbH
info@lab-wissen.de;
Tel: +49 (0) 69 8900 4008;
Fax: +49 (0) 69 8900 4007
Ferdinand-Porsche-Str. 2, 63073 Offenbach - Germany