



WEVER & DUCRÉ
LIGHTING

DEEP 1.0 PAR16

112120W0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Recessed

Signal White

IP20

Interior

495 lm

RAL 9003^a

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

CRI 90

OPTICAL

Wide Flood

Beam angle 48°

PHYSICAL

Diameter 84 mm

Height 102 mm

0.29 kg

wire springs

ELECTRICAL

100 - 240 V

LED Inset 6.5 W

Class 2

Safety distance 0.3 m

CUTOUT



Diameter 76-79 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 27 mm

Recessed depth 105 mm

^a Color may deviate slightly due to production conditions.



LIGHT DISTRIBUTION



[112120W0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

DEEP 1.0 PAR16

112120W0

CONE DIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	700	0.89
2	175	1.78
3	78	2.67
4	44	3.56
5	28	4.45

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50·58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50·58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50·58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50·58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50·52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50·52	9 0 5 2 2 7 S 4